

A Proof of the Security of Quantum Key Distribution

Eli Biham^{*}, Michel Boyer[†], P. Oscar Boykin[‡], Tal Mor[‡], and Vwani Roychowdhury[‡]

December 2, 1999

Abstract

We prove the security of quantum key distribution against the most general attacks which can be performed on the channel, by an eavesdropper who has unlimited computation abilities, and the full power allowed by the rules of classical and quantum physics. A key created that way can then be used to transmit secure messages in a way that their security is also unaffected in the future.

1 Introduction

Quantum key distribution [1] uses the power of quantum mechanics to suggest the distribution of a key that is secure against an adversary with unlimited computation power. Such a task is beyond the ability of classical information processing. The extra power gained by the use of quantum bits (quantum two-level systems) is due to the fact that the state of such a system cannot be cloned. On the other hand, the security of conventional key distribution is based on the (unproven) existence of various one-way functions, and mainly on the difficulty of factoring large numbers, a problem which is assumed to be difficult for a classical computer, and is proven to be easy for a hypothetical quantum computer [2].

Various proofs of security were previously obtained against collective attacks [5, 6, 3], and we continue this line of research here to prove the ultimate security of quantum key distribution (QKD), against any attack (under the conventional assumptions of QKD, as explained below). Note that the eavesdropper is assumed to have unlimited technology (e.g., a quantum memory, a quantum computer), while the legitimate users use practical tools (or more precisely, simplifications of practical tools).

To prove security against such a super-strong eavesdropper we develop some important technical tools and we reached some surprising results: we show new *information versus disturbance* results, where the power of quantum information theory is manifested in an intuitive and clear way. We show explicitly how the randomness of the bases, and the randomness of the choice of test-bits provides the desired security of QKD. We adopt and generalize sophisticated tools invented in [3]: a purification which simplifies Eve's states; a bound on accessible information (using Trace-Norm-Difference of density matrices) which avoids any complicated optimization of Eve's possible measurements; a connection between Eve's accessible information and the error-rate she induces. We add some more simplifications (which were not required in the analysis of collective attacks in [3]): a reduction to a scheme in which all qubits are used by Alice and Bob, and a usage of the symmetries of the problem under investigation.

Other security results/claims [7, 8, 14] were recently given (see a few more details in Appendix A). The security result of Lo and Chau [14] uses novel techniques and is very important, but it is somewhat limited. The QKD protocol which is analyzed in [14] requires that the legitimate users have quantum memories and quantum computers, technologies which are far from being available to the legitimate

^{*}Computer Science Department, Technion, Haifa 32000, Israel

[†]DIRO, Université de Montréal, Montréal, Canada

[‡]Dept. of Electrical Engineering, UCLA, Los Angeles, CA 90095-1594, USA

users. The security result of Mayers [7, 8] is equivalent to ours in the sense that it proves the security of a realistic protocol, against an unrestricted eavesdropper, and provides explicit bounds on the eavesdropper's information. There is no doubt that Mayers was the first to understand many of the difficulties and subtle points related to the security issues. The main problem with the proof of Mayers is its complexity, and strict formality. As a result, there was no consensus regarding its correctness and completeness. Recently, Mayers' proof was confirmed by a few researchers (e.g.[15]) and we believe that a consensus will soon be reached.

We follow the standard assumptions of QKD: 1) Alice and Bob share an unjammable classical channel. This assumption is usually replaced by the demand that Alice and Bob share a short secret key to be used for authenticating a standard classical channel (hence the protocol is then a quantum key expansion protocol). 2) Eve cannot attack Alice's and Bob's labs. She can only attack the quantum channel and listen to all transmissions on the classical channel. 3) Alice sends quantum bits (two level systems).

We prove the security of the Bennett-Brassard-84 (BB84) protocol [1], against any attack allowed by the rules of quantum physics. We prove the asymptotic security even for instances in which the error rate in the transmission from Alice to Bob is up to 7.56%; this allowed error-rate can be increased much further by choosing fixed codes and obtaining practical (rather than asymptotic) security result.

1.1 The BB84 Protocol and the used-bits-BB84 protocol

Alice and Bob use four possible quantum states in two bases (using "spin" notations, and connecting them to "computation basis" notations): (i) $|0_z\rangle \equiv |0\rangle$; (ii) $|1_z\rangle \equiv |1\rangle$; (iii) $|0_x\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)$; and (iv) $|1_x\rangle = \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle)$. We shall refer to these states as the BB84 states.

We prove in this paper the security of a simplified protocol in which only the relevant bits are discussed (we call it the "used-bits-BB84"). The proof of the original BB84 protocol follows immediately, due to a simple reduction, as we show in Appendix B.

Let us describe the used-bits protocol in detail, splitting it into *creating the sifted key* and *creating the final key from the sifted key*. This simplified protocol assumes that Bob has a quantum memory.

I. Creating the sifted key:

1. Alice and Bob choose a large integer $n \gg 1$. The protocol uses $2n$ bits.
2. Alice randomly selects two $2n$ -bit strings, b and i which are then used to create qubits: The string b determines the basis $0 \equiv z$, and $1 \equiv x$ of the qubits. The string i determines the value (0 or 1) of each of the $2n$ qubits (in the appropriate bases).

Alice generates $2n$ qubits according to her selection, and sends them to Bob via a quantum communication channel.

3. Bob tells Alice when he receives the qubits.
4. Alice publishes the bases she used, b ; this step should be performed only after Bob received all the qubits.

Bob measures the qubits in Alice's bases to obtain a $2n$ -bit string j .

We shall refer to the resulting $2n$ -bit string as the sifted key, and it would have been the same for Alice and Bob, $i = j$, if natural errors and eavesdropping did not exist.

II. Creating the final key from the sifted key:

1. Alice chooses at random a $2n$ -bit string s which has exactly n ones. There are $\binom{2n}{n}$ such strings to choose from.

2. From the $2n$ bits, Alice selects a subset of n bits, determined by the zeros in s , to be the test bits. Alice publishes the values of these test bits (given by a string i_T). The values of Bob's bits on the test bits are given by j_T .

The other n bits are the information bits (given by a string i_I). They are used for deriving a final key via error correction codes (ECC) and privacy amplification (PA) techniques.

[Alice shall send the ECC and PA information to Bob, hence Bob needs correct his errors and use PA to obtain a key equal to Alice's].

3. Bob verifies that the error rate $p_{test} = |i_T \oplus j_T|/n$ in the test bits is lower than some agreed error-rate $p_{allowed}$, and aborts the protocol if the error rate is larger.
4. Bob also publishes the values of his test bits (j_T). This is not crucial for the protocol, but it is done to simplify the proof.
5. Alice selects a linear ECC with 2^k code words of n bits, and a minimal Hamming distance d between any two words: an (n, k, d) code, and publishes it along with the ECC parities on the information bits; The strategy is that Alice announces the parity check matrix of an ECC, i.e., $r = n - k$ parity check strings of n bits: v_s , $s = 1, \dots, r$. She then announces r bits which are the parities of her string i_I with respect to the parity check matrix, which is $v_s \cdot i_I$ for all s . Bob doesn't announce anything. The condition on the ECC is that it corrects $t \geq (p_{allowed} + \epsilon_{rel})n$ errors, for some positive ϵ_{rel} . An ECC corrects t errors if $d \geq 2t + 1$, and thus $d \geq 2(p_{allowed} + \epsilon_{rel})n + 1$ must be chosen.
6. Bob performs the correction on the information bits.
7. Alice selects a privacy amplification function (PA) and publishes it. The PA strategy is to publish m n -bit strings and use the parities of the bits masked by these strings as the secret key. That is she announces *privacy-amplification-strings* v_s , where $s = r + 1, \dots, r + m$, of n bits each. The final secret key bits are $v_s \cdot i$. This strategy is similar to error correction except that the parities are kept secret.

The PA strings must be chosen such that the minimal distance $\hat{v}$, between any string in their span and any string in the span of their union with the ECC parity-check-strings, is at least $\hat{v} \geq 2(p_{allowed} + \epsilon_{sec})n$. Note that, by definition, the minimal distance of the space spanned by the ECC and PA strings, $d^\dagger$, is less than the above distance, hence if we demand $d^\dagger \geq 2(p_{allowed} + \epsilon_{sec})n$, the above criterion is automatically satisfied.

8. Bob performs the PA on the corrected information bits. The result obtained is the final key.

1.2 Eavesdropping

Eve attacks the qubits in two steps. First she lets all qubits pass through a device that tries to probe their state. Then, after receiving all the classical data, she measures the probe. She can gain nothing by measuring the probe earlier, since such a measurement is a special case of applying a unitary operation (it is the application of a measurement gate). Thus we can split Eve's attack into her transformation and her measurement.

Eve's transformation: The qubits can be attacked by Eve while they are in the channel between Alice and Bob. Eve can perform any attack allowed by the laws of physics, the most general one being any unitary transformation on Alice's qubits and Eve's probe. We are generous to Eve, allowing her to attack all the bits together (in practice, she usually needs to send the preceding qubit towards Bob before she has access to the next one).

Without loss of generality we assume that all the noise on the qubits, is caused by Eve, and can be used by her in any way she likes.

Eve's measurement: Eve keeps the probe in a quantum memory. After Eve receives *all* the classical information from Alice and Bob, including the bases of all bits, the choice of test bits, the test bits values, the ECC, the ECC parities, and the PA, she tries to guess the final key using her best strategy of measurement.

Eve's goal is to learn as much information as possible on the final key without causing Alice and Bob to abort the protocol due to a failure of the test. The task of finding Eve's optimal operation in these two steps is very difficult. Luckily, to prove security that task need not be solved, and it is enough to find bounds on Eve's optimal information (via any operation she could have done).

1.3 Security and Reliability

The issue of the security criterion is non-trivial since the obvious security criterion (that Eve's information given that the test passed, is small) does not work.

To be more precise, let $\mathcal{A}$ be a random variable presenting Alice's final key, $\mathcal{B}$ be a random variable presenting Bob's final key, and $\mathcal{E}$ a random variable representing a string in Eve's hands as result of her measurements. Let $\mathcal{T}$ be a random variable presenting if the test passed or failed. What one would like to obtain as a security criterion is $I(\mathcal{A}; \mathcal{E} \mid \mathcal{T} = \text{pass}) \leq A_{\text{info}} e^{-\beta_{\text{info}} n}$ with A and β (with any subscript) positive constants.

Unfortunately [8], the above bound is *not* satisfied in quantum cryptography. Given that the test is passed, Eve can still have full information. Consider the *swap attack*: Eve takes Alice's qubits and puts them into a quantum memory. She sends random BB84 states to Bob. Eve measures the qubits she kept after learning their bases, hence gets full information on Alice's final key. In this case, Bob will almost always abort the protocol because it is very unlikely that his bits will pass the test. However, even in the rare event when the test is passed, Eve still has full information on Alice's key. So, given the test is passed (a rare event), information is still m bits, and the above criterion cannot be satisfied.

In order to prove security we show that the event where the test is passed *and* Eve obtains meaningful information on the key is extremely unlikely. This means, that if Eve tries an attack that gives her non-negligible information on a final key she has to be extremely lucky in order to pass the test. Formally, the security criterion is:

$$\text{Prob}(\text{Test Passes and } I_{\text{Eve}} \geq A_{\text{info}} e^{-\beta_{\text{info}} n}) \leq A_{\text{luck}} e^{-\beta_{\text{luck}} n} . \quad (1)$$

Where $I_{\text{Eve}} \equiv I(\mathcal{A}; \mathcal{E} \mid i_T, c_T, b, s)$ is the information Eve has on the key, after the particular protocol values (i_T, j_T, b, s) are announced by Alice and Bob, and the probability is calculated over the cases such that $c_T = i_T \oplus j_T$ satisfies $|c_T| \leq np_{\text{allowed}}$. Note that Alice and Bob can increase the number of bits n as they like to increase security.

We show that the final m -bit key is reliable: the keys distilled by Alice and Bob are identical except for some exponentially small probability $A_{\text{rel}} e^{-\beta_{\text{rel}} n}$.

1.4 Structure of the Paper

The rest of the paper contains three main steps: In Section 2 we reduce the problem to a simpler problem of optimizing over all attacks symmetric to the bit values 0 and 1. In Section 3 we analyze the information bits in the bases actually used by Alice and Bob, and we prove our main *information versus disturbance* theorem: the eavesdropper information on the final key is bounded by the following probability: the probability of error if the *other* bases were used by Alice and Bob (this probability is well defined). We then obtain in Section 4 a bound on $\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} \mid i_T, c_T, b, s)$, and prove that this bound is exponentially small with n (so that the security criterion is satisfied). Various theorems are proven in the appendices.

2 Eve's Attack

In the protocol Alice sends a string i encoded in the bases of her choice b , and Bob measures a string j using the same set of bases. Eve prepares a probe in a known state, say $|0\rangle$. Eve applies a unitary transformation U on *all* the qubits and her probe and then she sends the disturbed qubits to Bob, while leaving her probe in her hands. The unitary transformation U is written in the basis b , $U(|0\rangle|i\rangle) = \sum_j |E'_{i,j}\rangle|j\rangle$, with $|E'_{i,j}\rangle$ the unnormalized states of Eve's probes if Alice sent $|i\rangle$, and Bob received $|j\rangle$.

Recall that the choice of 0/1 is random. As a result, any attack chosen by Eve can be replaced by an equivalent attack which is as good, with i replaced by $i \oplus k$ and with j replaced by $j \oplus k$. Thus, any attack chosen by Eve can also be replaced by an equivalent symmetric attack which is as good (as described below). The symmetrization does not change the induced error-rate as we show below. It can improve Eve's final information on the common secret key, and thus, if the optimal attack is asymmetric, there is also an equivalent symmetric attack which is optimal. Thus, the optimal attack can be assumed to be symmetric (WLG), and we therefore need to bound Eve's information only for attacks symmetric to 0/1.

The symmetrization is performed using bit-wise operations: Given any transformation of Eve, Eve symmetrizes it as follows: For each qubit $|q_l\rangle$, she creates a qubit $|w_l\rangle = H|0\rangle = \frac{1}{\sqrt{2}}(|0_z\rangle + |1_z\rangle)$, and performs a pseudo-controlled-NOT transform on the result of this bit and $|q_j\rangle$: if $|w_j\rangle = 0$: leave $|q_j\rangle$ as is. Otherwise negate it (i.e., rotate by 180 degrees). After the application of U , she performs the inverse of this pseudo-controlled-NOT transform. The gate needs to negate the bit in both x and z bases. In fact, Control- $(\sigma_x \sigma_z)$ on this ancillary qubit and the data qubit performs this transformation. The 0/1 symmetrization ensures that the errors are independent of the values 0 or 1 that Alice sends (in either basis). The overall attack on all qubits is then described by $U^{sym}(|0\rangle|i\rangle) = \sum_j |E'^{sym}_{i,j}\rangle|j\rangle$ with E'^{sym} which can be written using E' as follows:

$$|E'^{sym}_{i,j}\rangle = \frac{1}{\sqrt{2^{2n}}} \sum_m (-1)^{(i \oplus j) \cdot m} |m\rangle |E'_{i \oplus m, j \oplus m}\rangle. \quad (2)$$

To prove that the 0/1 symmetrization does not change the average error-rate is obvious since Eve can always project onto one particular m (and destroy the symmetry) by measuring $|m\rangle$, and any such projection leads to the same attack (up to a shift of i and j by m). It is also obvious that the symmetric attack cannot be worse (for Eve) in terms of Eve's information (for the same reason). Clearly, it can only increase Eve's information since she does not have to measure m but can also do other things.

Later on Eve obtains *all* classical information sent by Alice and Bob. Eve learns b (the bases) and s (which bits are the test bits and which are the information bits). She also learns the values of the test bits i_T and j_T . We also use i_I and j_I to denote the values of the information bits. Once the additional data regarding the bases and the values of the test bits is given to Eve, this data modifies her probes' states. We define $|\psi_{i_I}\rangle$ to be the state of Eve+Bob if Alice chose a bases b , an order s , and values $i_T i_I$, Eve's attack is U^{sym} , and Bob received j_T in his measurement on the test bits. Formally,

$$|\psi_{i_I}\rangle = \frac{1}{\sqrt{P(j_T|i_T, i_I, b, s)}} [\langle j_T | U^{sym}(|0\rangle)_{Eve} (|i_T\rangle|i_I\rangle)_{Alice}] \quad (3)$$

We define $|E_{i_I, j_I}\rangle$, Eve's states *for a given* classical data regarding (i_T, j_T, s, b) , by writing $|\psi_{i_I}\rangle = \sum_{j_I} |E_{i_I, j_I}\rangle|j_I\rangle$. If E_{ij} is obtained from an attack E'_{ij} and for that attack, E'^{sym}_{ij} is obtained from the symmetric attack E'^{sym}_{ij} , then E_{ij} also satisfies Eq. 2 with E replacing E' . See a proof in Appendix C.

3 Information Versus Disturbance

In this section we analyze the information bits alone (for a given symmetric attack U^{sym} , a given input i_T and outcome j_T on the test bits, and given bases b and choice of test bits s). Our result here applies for any U^{sym} , hence in particular for the optimal one. The optimization over Eve's measurement is avoided by using the fact that trace-norm of the difference of two density matrices provides an upper bound on the accessible information one could obtain when having the two density matrices as the possible inputs.

3.1 Eve's State

When Alice sends a state $|i_I\rangle$ for the information bits (written in the basis actually used by her and Bob for these bits), the state of Eve and Bob together, $|\psi_{i_I}\rangle = \sum_{j_I} |E_{i_I, j_I}\rangle |j_I\rangle$ is fully determined by Eve's attack and by the data regarding the test bits. Eve's state in that case is fully determined by tracing-out Bob's subsystem $|j_I\rangle$ from the Eve-Bob state, and it is

$$\rho^{i_I} = \sum_{j_I} |E_{i_I, j_I}\rangle \langle E_{i_I, j_I}| ,$$

calculated given i_T and j_T . This state in Eve's hands is a mixed state.

3.2 Purification and a related Orthogonal Basis

We can “purify” the state while giving more information to Eve by assuming she keeps the state

$$|\phi_{i_I}\rangle = \sum_{j_I} |E_{i_I, j_I}\rangle |i_I \oplus j_I\rangle$$

where we introduce another subsystem for the purification.

This state is at least as informative to Eve as ρ^{i_I} is. This is because the density matrix is exactly the same if Eve ignores the $i \oplus j$ register of ϕ . Thus, any information Eve can obtain from her mixed state is bounded by the information she could get if the purified state was available to her.

Since we deal here only with the information bits, we can drop the subscript I when there is no risk of confusion, and we write: $\rho^i = \sum_j |E_{i,j}\rangle \langle E_{i,j}|$, and $|\phi_i\rangle = \sum_j |E_{i,j}\rangle |i \oplus j\rangle$. We shall retain the index when we consider both Information and Test bits.

We define an orthogonal basis $|\eta\rangle$, and show that it is possible to compute a bound on Eve's information on the information bits, once the purified states are written in this basis.

Definition 3.1

$$|\eta_i\rangle = \frac{1}{2^n} \sum_l (-1)^{i \cdot l} |\phi_l\rangle ; d_i^2 = \langle \eta_i | \eta_i \rangle ; \hat{\eta}_i = \eta_i / d_i$$

Using the above definitions and $(1/2^n) \sum_l (-1)^{(i \oplus j) \cdot l} = \delta_{ij}$, Eve's purified state can be rewritten as:

$$|\phi_i\rangle = \sum_l (-1)^{i \cdot l} |\eta_l\rangle \tag{4}$$

Lemma 3.1 η_i 's form an orthogonal basis, i.e., $\langle \eta_k | \eta_l \rangle = 0$ for $k \neq l$.

Proof: See Appendix D. It should be noted the above lemma is the only place where 0/1 symmetry is explicitly made use of.

3.3 Eve's State and Probability of Errors Induced on Information Bits

In this subsection we first show that the probability of any error string Eve would have induced if the conjugate basis was used for the information bits, is a simple function of d_i 's (of Definition 3.1).

For any attack $P(j_I = i_I \oplus c_I \mid i_I, i_T, j_T, b, s) = \langle E_{i_I, i_I \oplus c_I} | E_{i_I, i_I \oplus c_I} \rangle$, and thus, the error distribution in the information bits is

$$P(c_I \mid i_T, j_T, b, s) \triangleq \frac{1}{2^n} \sum_{i_I} P(|j_I\rangle = |i_I \oplus c_I\rangle \text{ given } i_I, i_T, j_T, b, s) = \frac{1}{2^n} \sum_i \langle E_{i_I, i_I \oplus c_I} | E_{i_I, i_I \oplus c_I} \rangle.$$

the average probability of an error syndrome c for the information bits (when the test bits, basis and sequence are given).

Due to the linearity of quantum mechanics, given Eve's attack in one basis we can write Eve's attack in any other basis, and in particular, in a basis where the x/z bases of each information qubit are interchanged. Let an input string be the same as the original, but with the bases of the information bits switched, i.e., $|i_T, i_I^o\rangle$, and let the output bits be $|j_T, j_I^o\rangle$ in that switched bases. If Alice and Bob used the conjugate basis for each of the information qubits (while using the same bases as before for the test bits), and Eve used the same attack, then the error distribution in the conjugate basis (over the information bits) is

$$P(c_I^o \mid i_T, j_T, b, s) \triangleq \frac{1}{2^n} \sum_{i_I^o} P(|j_I^o\rangle = |i_I^o \oplus c_I^o\rangle \text{ given } i_I^o, i_T, j_T, b, s).$$

The following lemma shows that the probability of an error syndrome c , if the conjugate bases were used, equals the coefficients d_c when writing the purification of Eve's states in the basis $|\eta_c\rangle$.

Lemma 3.2

$$P(c_I^o \text{ given } i_T, j_T, b, s) = d_{c_I}^2. \quad (5)$$

Proof: See Appendix E.

This is the only place where the properties of quantum mechanics are used, and this result is later on translated into an *information versus disturbance* result. The rest of the proof is based on probability theory and information theory.

3.4 Bounds on Eve's Information

In this subsection we improve upon a result based on [3]. Eve's information on a particular bit of the final key (even if all other bits of the final key are given to her) is bounded. We take into consideration the error-correction data that is given to Eve, and we do it more efficiently than in [3], hence we obtain a much better threshold for the allowed error-rate.

Let us first discuss one-bit final key, defined to be the parity of substring of the input i . The substring is defined using a mask v , meaning that the secret key is $v \cdot i$ (so v tells us the subset of bits whose parity is the final key). See Appendix F for more formal explanation of ECCs. Eve does not know i , but she learns the error correcting code $\mathcal{C}$ used by Alice and Bob as well as v and the parity bits ξ sent by Alice to help Bob correct the sequence he received. All the possible inputs i that have the correct parities ξ for the code $\mathcal{C}$ form a set denoted $\mathcal{C}_\xi$.

When the purification of Eve's state is given by $|\phi_i\rangle$ the density matrix is $\rho^i = |\phi_i\rangle\langle\phi_i|$. In order to guess the key $\hat{b} = v \cdot i$, Eve must now distinguish between two *ensembles* of states: the ensemble of (equally likely) states ρ^i with $i \in \mathcal{C}_\xi$ and key $\hat{b} = v \cdot i = 0$, and the ensemble of (equally likely) states ρ^i with $i \in \mathcal{C}_\xi$ and key $\hat{b} = v \cdot i = 1$. For $\hat{b} \in \{0, 1\}$ these ensembles are represented by the following density matrices:

$$\rho_{\hat{b}} = \frac{1}{2^{n-(r+1)}} \sum_{\substack{i \in \mathcal{C}_\xi \\ i \cdot v = \hat{b}}} \rho^i$$

and Eve's goal is to distinguish between them. A good measure for their distinguishability is the optimal mutual information (known as the accessible information) that one could get if one needs to guess the bit b by performing an optimal measurement to distinguish between the ρ_b . We call this Shannon Distinguishability (SD) to emphasize that it is a distinguishability measure, and $SD \equiv \text{opt}\{I(\mathcal{A}_j; \mathcal{E}|i_T, j_T, b, s)\}$ where the optimization is over all possible measurements.

In the same way that v acts as a mask and the secret bit is $v \cdot i$, the error-correction data also acts as masks: the r "parity-check strings" $v_1, v_2, \dots, v_r$, and the parities: $\{v_1 \cdot i, v_2 \cdot i, \dots, v_r \cdot i\}$ are given to Eve. Let us assume (WLG) that these parity-check strings are linearly independent. Eve also knows the parity of any linear combination of the r parity strings, e.g., $(v_1 \oplus v_2) \cdot i$. As result, a total of 2^r parity strings and parity bits are known to Eve. Let us take s to be an index running from 0 to $2^r - 1$, so we call the set of all these 2^r parity strings S_s , and $v_s \in S_s$ means that v_s is in this set.

Let $\hat{v}$ be the minimum Hamming distance between v and any (error correction) parity string v_s . [The minimal Hamming weight of $v \oplus v_s$ when the minimum is over all strings $v_s \in S_s$]. Then, for Eve's purified states $|\phi_i\rangle = \sum_l (-1)^{i \cdot l} d_l |\hat{\eta}_l\rangle$, we obtain that

Lemma 3.3 The Shannon distinguishability between the parity 0 and the parity 1 of the information bits over any PA string, v , is bounded above by the following inequality:

$$SD_v \leq \alpha + \frac{1}{\alpha} \sum_{|l| \geq \frac{\hat{v}}{2}} d_l^2, \quad (6)$$

where α is any positive constant, and SD_v is the optimal mutual information that Eve can obtain regarding the parity bit defined by the string v (given the test and unused bits).

Proof: See Appendix G.

This gives an upper bound for Eve's information about the bit defined by this privacy amplification string v . In order to prove security in case of m bits in the final key, we start by proving security of each bit when we assume that Eve is given the ECC information and in addition, she is also given the values of all the other bits of the key. This is like using a code with $r + m - 1$ independent parity check strings, or like using less code words. Since r does not appear in the above bound, replacing r by $r + m - 1$ leaves the same result as before, $SD_v \leq \alpha + \frac{1}{\alpha} \sum_{|l| \geq \frac{\hat{v}}{2}} d_l^2$, as a bound on Eve's information on (any) one bit of the final key (but probably causes a decrease in $\hat{v}$).

3.5 Eve's Information versus the Induced Disturbance

We have already shown in Eq.(5) that $P(c_I^o \text{ given } i_T, j_T, b, s) = d_{c_I}^2$. Thus,

$$SD_v \leq \alpha + \frac{1}{\alpha} \sum_{|c_I| \geq \frac{\hat{v}}{2}} P(c_I^o | i_T, j_T, b, s). \quad (7)$$

This equation bounds the information of Eve using the probability of the error syndromes in the other basis, and it completes the "information versus disturbance" result of our proof. Previous security proofs (for simpler attacks), such as [4, 6, 3] are also based on various "information versus disturbance" arguments, since the non-classicality of QKD is manifested via such arguments.

The result is expressed using classical terms: Eve's information is bounded using the probability of error strings with large Hamming weight. If only error strings with low weight have non-zero probability, Eve's information goes to zero. Such a result is a "low weight" property and it resembles a similar result with this name which was derived by Yao [12] for the security analysis of quantum oblivious transfer. Henceforth we no longer concern ourselves with the delicate issues of quantum mechanics.

From this point on we want to use standard information theory and probability notations. Shannon Distinguishability is the optimal mutual information between Eve's bits ($\mathcal{E}$) and Alice's j^{th} bit

$(\mathcal{A}_j)$ (when all other PA bits are given together with the ECC data and test data). Therefore, $I(\mathcal{A}_j; \mathcal{E} | i_T, j_T, b, s) \leq \alpha + \frac{1}{\alpha} \sum_{|c_I| \geq \frac{\hat{v}}{2}} P(c_I^o | i_T, j_T, b, s)$.

When summing over the m bits of the key, the total information Eve receives on the final m -bit key is bounded by

$$I(\mathcal{A}; \mathcal{E} | i_T, j_T, b, s) \leq m \left(\alpha + \frac{1}{\alpha} \sum_{|c_I| \geq \frac{\hat{v}}{2}} P(c_I^o | i_T, j_T, b, s) \right), \quad (8)$$

as explained in Appendix H.

If $\alpha = \sqrt{\sum_{|c_I| \geq \frac{\hat{v}}{2}} P(c_I^o | i_T, j_T, b, s)}$, then $I(\mathcal{A}; \mathcal{E} | i_T, j_T, b, s) \leq 2m \sqrt{\sum_{|c_I| \geq \frac{\hat{v}}{2}} P(c_I^o | i_T, j_T, b, s)}$, however, to derive the security criterion we need not fix α yet.

4 Completing the Security Proof

In this section we analyze the attack on the test and information together $U^{sym}[(|0\rangle)_{Eve}(|i_T\rangle|i_I\rangle)_{Alice}] \equiv \sum_{j_T, j_I} |E'_{i_T, i_I, j_T, j_I}\rangle |j_T\rangle |j_I\rangle$. For these states, we will bound a weighted average of Eve's information: $\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s)$. We show that the above bound is small and hence that security is achieved. Note that c_T replaces j_T from this point forward (when i_T is given). Recall that $c_T = i_T \oplus j_T$, so once c_T is known j_T is uniquely given. We define C_I and C_T to be the random variables getting the values c_I and c_T respectively.

4.1 Exponentially-Small Bound on Eve's information

We generalize here previous proofs [18, 5, 3] that information on parity bits is exponentially small, to be applicable for the joint attack.

The maximum error rate that still passes the test is p_{allowed} (or p_a). Also recall that $\mathcal{T}$ denotes the random variable for the test. Making use of Eq. 8 we get:

Lemma 4.1

$$\sum_{i_T, c_T} P(\mathcal{T} = \text{pass}, i_T, c_T | b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq m \left(\alpha + \frac{1}{\alpha} P\left(\left|\frac{C_I^o}{n}\right| > \frac{\hat{v}}{2}\right) \cap \left(\left|\frac{C_T}{n}\right| \leq p_{\text{allowed}}\right) | b, s \right)$$

Proof: The Proof is in Appendix I.

For an ϵ (called earlier ϵ_{sec}) such that $\hat{v} \geq 2n(p_{\text{allowed}} + \epsilon)$ we get the following bound:

$$\sum_{i_T, c_T} P(\mathcal{T} = \text{pass}, i_T, c_T | b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq m \left(\alpha + \frac{1}{\alpha} P\left[\left(\left|\frac{C_I^o}{n}\right| > p_a + \epsilon\right) \cap \left(\left|\frac{C_T}{n}\right| \leq p_a\right) | b, s \right] \right)$$

Thus far, there is nothing that causes the bound on the right hand side to be a small number. The result above is true even if Eve is told in advance the bases of Alice and Bob (the string b), or if she is told in advance which are the test bits and which are the used bits (the string s), two cases in which Eve easily obtains full information.

Only Eve's lack of knowledge regarding the random b and s provides an exponentially small number at the right hand side. Since Eve must fix her attack *before* she knows the basis or order, we compute the average information for a fixed attack over all bases and orders. This averaging has the fortunate side effect of removing the conjugation on C_I :

Lemma 4.2

$$\sum_{i_T, c_T, b} P(\mathcal{T} = \text{pass}, i_T, c_T, b | s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq m \left(\alpha + \frac{1}{\alpha} \frac{1}{2^{2n}} \sum_b P\left[\left(\left|\frac{C_I}{n}\right| > p_a + \epsilon\right) \cap \left(\left|\frac{C_T}{n}\right| \leq p_a\right) | b, s \right] \right) \quad (9)$$

Proof: The Proof is in Appendix J.

By averaging over all values of the order s , and assigning a value to the free parameter α we get:

Lemma 4.3

$$\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} \mid i_T, c_T, b, s) \leq 2m \sqrt{\frac{1}{2^{2n}} \sum_b P[(\frac{|C_I|}{n} > p_a + \epsilon) \cap (\frac{|C_T|}{n} \leq p_a) | b]}. \quad (10)$$

Proof: The Proof is in Appendix K.

We define $h_b \equiv P[(\frac{|C_I|}{n} > p_a + \epsilon) \cap (\frac{|C_T|}{n} \leq p_a) | b]$, and then:

$\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} \mid i_T, c_T, b, s) \leq 2m \sqrt{\frac{1}{2^{2n}} \sum_b h_b}$. The current bound can be dealt with the help of a random sampling theorem (Hoeffding's law of large numbers[10]). For a long string, the test bits and the information bits should have similar number of errors if the test is picked at random. The probability that they have different numbers of errors should go to zero exponentially fast as shown in the following lemma.

Lemma 4.4 For any $\epsilon > 0$, $h_b \leq 2e^{-\frac{1}{2}n\epsilon^2}$.

Proof: See Appendix L.

As a **Corollary** we get $\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} \mid i_T, c_T, b, s) \leq 2m \sqrt{2e^{-\frac{1}{2}n\epsilon^2}} = Ae^{-\beta n}$, with $A = 2m\sqrt{2}$ and $\beta = \epsilon^2/4$.

Using $I_{Eve} \equiv I(\mathcal{A}; \mathcal{E} \mid i_T, c_T, b, s)$ and the above bound we obtain the security criterion (see Appendix N):

$$Prob(\text{Test Passes and } I_{Eve} \geq A_{\text{info}} e^{-\beta_{\text{info}} n}) \leq A_{\text{luck}} e^{-\beta_{\text{luck}} n} \quad (11)$$

with $A_{\text{info}} = A_{\text{luck}} = \sqrt{A}$ and $\beta_{\text{info}} = \beta_{\text{luck}} = \beta/2$.

When choosing $\epsilon = \epsilon_{\text{rel}}$ in Lemma 4.4, that Lemma also provides the proof that, once the test passes, there are no more than $(p_a + \epsilon_{\text{rel}})n$ errors in the information string (except for exponentially small probability $2e^{-\frac{1}{2}n\epsilon^2}$), so that the ECC corrects these errors. Thus $A_{\text{rel}} = 2$ and $\beta_{\text{rel}} = \epsilon_{\text{rel}}^2/2$, in the reliability criterion.

The above bound of Eve's information is exponentially small, but it assumes that ECC codes with the desired properties exist. We present an asymptotic result of security and reliability using random linear codes (RLC) in Appendix O where we analyze RLC and we show that such a code provides an asymptotic reliability and security, for an allowed error-rate below 7.56%.

5 Summary

We proved the security of the Bennett-Brassard (BB84) protocol for quantum key distribution. Our proof is based on information-versus-disturbance, on the optimality of symmetric attacks, on laws of large numbers, and on various techniques that simplifies the analysis of the problem.

References

- [1] C. H. Bennett and G. Brassard, in *Proceedings of IEEE International Conference on Computers, Systems and Signal Processing* (IEEE, Bangalore, India, 1984), pp. 175–179.
- [2] P. W. Shor. “Polynomial-time algorithms for prime factorization and discrete logarithms on a quantum computer”, *SIAM J. Comput.*, 26:1484–1509, 1997
- [3] E. Biham, M. Boyer, G. Brassard, J. van de Graaf, and T. Mor, “Security of Quantum Key Distribution Against All Collective Attacks”, LANL e-print quant-ph/9801022.

- [4] C. Fuchs, N. Gisin, R.B. Griffiths, C.S. Niu and A. Peres, “Optimal eavesdropping in quantum cryptography. I. Information bound and optimal strategy”, *Phys. Rev. A* **56**, 1997. p.1163-72
- [5] E. Biham and T. Mor, “Security of quantum cryptography against collective attacks”, *Phys. Rev. Lett.* **78**, 2256 (1997).
- [6] E. Biham and T. Mor, “Bounds on information and the security of quantum cryptography”, *Phys. Rev. Lett.* **79**, 4034 (1997).
- [7] D. Mayers, “Quantum key distribution and string oblivious transfer in noisy channel”, *Proc. of Crypto’96, LNCS* **1109**, 343 (1996), 343-357.
- [8] D. Mayers, “Unconditional security in quantum cryptography”, LANL e-print, quant-ph/9802025.
- [9] R. G. Gallager, *Low-Density Parity Check Codes*, MIT press, 1963, Chapter 2.
- [10] W. Hoeffding, “Probability inequalities for sums of bounded random variables”, *American Statistical Association Journal*, **58**, 13 (1963).
- [11] L. Devroye, L. Györfi, G. Lugosi, *A probabilistic theory of pattern recognition*, p 589, New York : Springer, 1996.
- [12] A. Yao, In *Proceedings of the 26th Symposium on the the Theory of Computing*, June 1995, 67-75.
- [13] D. Mayers, “On the security of the quantum oblivious transfer and key distribution protocols”, *Proc. of Crypto’95, LNCS* **963** (1995), 124-135.
- [14] H. K. Lo and H. F. Chau, “Unconditional security of quantum key distribution over arbitrarily long distances”, *Science*, vol.283 (1999), p2050-6.
- [15] P. Shor, private communication.
- [16] M. Ben-Or, a talk given in a mini-workshop organized by Asher Peres (Technion, April 1999).
- [17] D. Deutsch, A.K. Ekert, R. Jozsa, C. Macchiavello, S. Popescu and A. Sanpera, *Physical Review Letters* **77**, 2818 (1996).
- [18] C. H. Bennett, T. Mor, and J. A. Smolin, “Parity bit in quantum cryptography”, *Phys. Rev. A* **54**, 2675 (1996).
- [19] T. Mor, “Reducing quantum errors and improving large scale quantum cryptography”, LANL e-print, quant-ph/9608025.
- [20] C. A. Fuchs and J. van der Graaf, “Cryptographic distinguishability measures for quantum-mechanical states”. *IEEE Transactions on Information Theory*, vol.45, (no.4), IEEE, May 1999. p.1216-27. LANL e-print, quant-ph/9712042.
- [21] T. Cover, J. Thomas, *Elements of Information Theory*, A Wiley-Interscience Publication, 1991.

A Comparison to Other approaches to the security of QKD

A proof of security of a non practical QKD (based on the use of quantum computers by the legitimate users) is provided in [14]; it is based on the assumptions of fault tolerant quantum computation, hence it can not provide yet a bound on Eve’s information. Apart from this, it is a very strong proof. The work of Lo and Chau continues previous works on quantum privacy amplification [17] and [19].

A security claim equivalent to ours (for the same QKD protocol of [1]) was announced in Crypto96 [7] and its details (and some corrections) are given later on, in publicly announced drafts [8]. It is obtained using different tools, based on the security of quantum oblivious transfer (given bit commitment) [12, 13].

Our work provides a rather simple security proof based on the intuitive concept of information versus disturbance.

Our result does not suffer from any problem related to the use of fault-tolerant computation, which in our case refers to the regular classical fault-tolerant computation used in classical information processing steps of any classical protocol: since we discuss probabilities, the only effect of a coherent error on the classical computation is to add some extremely small probability of error $P(\text{coherent classical noise})$ to the final probability of failure (called P_{luck}). On the other hand, doing the same for the quantum coherent noise in the protocol [14] is not obvious, and still requires a proof.

There are two recent suggestions to attack the security problem using analogy to quantum error correction [15] and using compression and random sampling [16], but we have yet to see written drafts of these ideas.

B Security of BB84

In the paper we prove that used-bits-BB84 is secure. Let us now present the original BB84 protocol and prove, by reduction, that its security follows immediately from the security of the used-bits-BB84 protocol.

The differences between the protocols are only in the first part:

I. Creating the sifted key:

1. Alice and Bob choose a large integer $n \gg 1$, and a number δ_{num} , such that $1 \gg \delta_{\text{num}} \gg 1/\sqrt{(2n)}$. The protocol uses $n'' = (4 + \delta_{\text{num}})n$ bits.
2. Alice randomly selects two n'' -bit strings, b and i , which are then used to create qubits: The string b determines the basis $0 \equiv z$, and $1 \equiv x$ of the qubits. The string i determines the value (0 or 1) of each of the n'' qubits (in the appropriate bases).
3. Bob randomly selects an n'' -bit string, b' , which determines Bob's later choice of bases for measuring each of the n'' qubits.
4. Alice generates n'' qubits according to her selection of b and i , and sends them to Bob via a quantum communication channel.
5. After receiving the qubits, Bob measures in the basis determined by b' .
6. Alice and Bob publish the bases they used; this step should be performed only after Bob received all the qubits.
7. All qubits with different bases are discarded by Alice and Bob. Thus, Alice and Bob finally have $n' \approx n''/2$ bits for which they used the same bases. The n' -bit string would be identical for Alice and Bob if Eve and natural noise do not interfere.
8. Alice selects the first $2n$ bits from the n' -bit string, and the rest of the n' bits are discarded. If $n' < 2n$ the protocol is aborted.

We shall refer to the resulting $2n$ -bit string as the sifted key.

The second part of the protocol is identical to the second part of the used-bits-BB84 protocol. To prove that BB84 is secure let us modify BB84 by a few steps in a way that each step can only be helpful to Eve, and the final protocol is the used-bits-BB84.

Recall that Alice and Bob choose their strings of basis b and b' in advance. Recall the the two strings are random. Thus, the first modification below has no influence at all on the security or the analysis of the BB84 protocol. Note that after the first modification Alice knows the un-used bits in advance. The second modification is done in a way that Eve can only gain, hence security of the resulting protocol provides the security of BB84. The third modification is only “cosmetic”, in order to derive precisely the used-bits-BB84 protocol. This modification changes nothing in terms of Eve’s ability.

- Let Bob have a quantum memory. Let Alice choose b' instead of Bob at step 3. When Bob receives the qubits at step 5, let him keep the qubits in a memory, and tell Alice he received them. In step 6, let Alice announce b' to Bob, and Bob measure in bases b' .

Bob immediately knows which are the used and the un-used bits (as follows directly from announcing b and b'). Steps 7 and 8 are now combined since Alice and Bob know all the un-used bits already, and they ignore them, to be left with $2n$ bits.

- Let Alice generate and send to Bob only the used bits in step 4, and let her ask Eve to send the un-used bits (by telling her which these are, and also the preparation data for the relevant subsets, that is— $b_{un-used}$ and $i_{un-used}$). Knowing which are the used bits, and knowing their bases $b_{un-used}$ and values $i_{un-used}$ can only help Eve in designing her attack U' .

Since Bob never uses the values of the unused bits in the protocol (he only ignores them), he doesn’t care if Eve doesn’t provide him these bits or provide them to him without following Alice’s preparation request.

After Bob receives the used and unused bits, let him give Eve the unused qubits (without measuring them), and ask her to measure them in bases $b'_{un-used}$. Having these qubits can only help Eve in designing her optimal final measurement.

Since Bob never use the values of the unused bits in the rest of the protocol, he doesn’t care if Eve doesn’t provide him these values correctly or at all.

- Since Alice and Bob never made any use of the unused bits, Eve could have them as part of her ancilla to start with, and Alice could just create $2n$ bits, send them to Bob, and then tell him the bases.

The protocol obtained after this reduction, is a protocol in which Eve has full control on her qubits and on the unused qubits. Alice and Bob have control on the preparation and measurement of the used bits only. This is the used-bits BB84, for which we prove security in the text.

One important remark is that the exponentially small probability that $n' < 2n$ in Step 8 (so that the protocol is aborted due to insufficient number of bits in the sifted key) now becomes a probability that the reduction fails.

Another important remark is that the issue of high loss rate of qubits (e.g., due to losses in transmission or detection) can also be handled via the same reduction. Thus, our proof applies also to a more practical BB84 protocol where high losses are allowed.

By the way, another practical aspect is imperfect sources (in which the created states are not described by a two-level system). This subject is the issue of recent subtlety regarding the security of practical schemes, and it is not discussed in this current work.

C Symmetrization

We prove the optimality of 0/1 symmetrization. It is also shown that the symmetrized attacks retain 0/1 symmetrization even after the test bits measured.

The fundamental reason symmetrization works, is because Alice sends Bob bits that have a great deal of symmetry before the key is defined. For instance, Alice sends 0 with probability half, and likewise 1. So, Eve can gain nothing by assuming a particular string was sent or by optimizing her attack for a particular string. We discuss the symmetrization of the attack U , on $2n$ qubits. We use $|E_{i_T, i_I, j_T, j_I}\rangle$ for $|E'_{ij}\rangle$, when both test and information bits are considered together.

Eve's attack over all the bits is defined:

$$U|0\rangle|i\rangle = \sum_j |E'_{i,j}\rangle|j\rangle \quad (12)$$

The following symmetric attack is defined:

$$|E'_{i,j}{}^{sym}\rangle = \frac{1}{\sqrt{2^{2n}}} \sum_m (-1)^{(i \oplus j) \cdot m} |m\rangle |E'_{i \oplus m, j \oplus m}\rangle \quad (13)$$

This symmetric attack is at least as good as the original attack: Eve could, as part of her attack, measure the bits of $|m\rangle$. She would then collapse her attack to $|E'_{i \oplus m, j \oplus m}\rangle$ uniformly distributed over m . If the attack $|E'_{i,j}\rangle$ was optimal and if i, j are uniformly distributed, then $|E'_{i \oplus m, j \oplus m}\rangle$ is also optimal as it only represents a shift in Alice's (already random) choice of bits. From Eve's perspective the symmetrization is simple. She prepares the register: $\sum_m |m\rangle$ and uses it as the control bits in a *Controlled* – $(\sigma_x \sigma_z)$ (i.e., the controlled-NOT described in Section 2) onto the bits intended for Bob. Eve then applies her unsymmetrized attack $|E'_{i,j}\rangle$. Following this she un-applies the bit flips by *Controlled* – $(\sigma_z \sigma_x)$.

Now we show that information bits are still symmetric after test bits are measured: If we first symmetrize the test then the information, we will get the following:

$$|E_{i_I, i_T, j_I, j_T}^s\rangle = \frac{1}{2^n} \sum_{m_I, m_T} |m_I\rangle |m_T\rangle (-1)^{(i_I \oplus j_I) \cdot m_I} (-1)^{(i_T \oplus j_T) \cdot m_T} |E_{i_I \oplus m_I, i_T \oplus m_T, j_I \oplus m_I, j_T \oplus m_T}\rangle \quad (14)$$

Since $i = i_I i_T$, $j = j_I j_T$, and $m = m_I m_T$, (13) becomes:

$$|E_{i_I, i_T, j_I, j_T}^s\rangle = \frac{1}{2^n} \sum_{m_I, m_T} |m_I\rangle |m_T\rangle (-1)^{((i_I i_T) \oplus (j_I j_T)) \cdot (m_I m_T)} |E_{i_I \oplus m_I, i_T \oplus m_T, j_I \oplus m_I, j_T \oplus m_T}\rangle \quad (15)$$

These two are identical because:

$$(-1)^{((i_I i_T) \oplus (j_I j_T)) \cdot (m_I m_T)} = (-1)^{(i_I \oplus j_I) \cdot m_I} (-1)^{(i_T \oplus j_T) \cdot m_T}$$

Hence the bit symmetrization is applied independently on test and information. This is used in the paper when we show that the basis $|\eta_i\rangle$ is an orthogonal basis.

So now we write the $|E_{i_I, j_I}^s\rangle$ which is the attack once the test is given:

$$|E_{i_I, j_I}^s\rangle = \frac{1}{\sqrt{p(j_T|i_I, i_T)}} |E_{i_I, i_T, j_I, j_T}^s\rangle \quad (16)$$

where $p(j_T|i_I, i_T) = \sum_{j_I} \langle E_{i_I, i_T, j_I, j_T}^s | E_{i_I, i_T, j_I, j_T}^s \rangle$. This can be expanded in the following manner:

$$\begin{aligned} p(j_T|i_I, i_T) &= \sum_{j_I} \langle E_{i_I, i_T, j_I, j_T}^s | E_{i_I, i_T, j_I, j_T}^s \rangle \\ &= \frac{1}{2^{2n}} \sum_{j_I} \sum_{m_I, m_T} \langle E_{i_I \oplus m_I, i_T \oplus m_T, j_I \oplus m_I, j_T \oplus m_T} | E_{i_I \oplus m_I, i_T \oplus m_T, j_I \oplus m_I, j_T \oplus m_T} \rangle \\ &= \frac{1}{2^{2n}} \sum_{c_I} \sum_{m'_I, m_T} \langle E_{m'_I, i_T \oplus m_T, c_I \oplus m'_I, j_T \oplus m_T} | E_{m'_I, i_T \oplus m_T, c_I \oplus m'_I, j_T \oplus m_T} \rangle \end{aligned}$$

So in fact, $p(j_T|i_I, i_T)$ is independent of i_I so we may write:

$$|E_{i_I, j_I}^s\rangle = \frac{1}{\sqrt{p(j_T|i_T)}} |E_{i_I, i_T, j_I, j_T}^s\rangle \quad (17)$$

We can imagine that the information bit symmetrization is applied after the test symmetrization, and after the measurement of the test bits has been done. Of course one cannot apply the information bit symmetrization after the information bits have been measured, because the attack is fixed after all bits have been measured.

$$\begin{aligned} |E_{i_I, j_I}^{s_T}\rangle &= \frac{1}{\sqrt{p(j_T|i_T)}} |E_{i_I, i_T, j_I, j_T}^{s_T}\rangle \\ &= \frac{1}{\sqrt{p(j_T|i_T)}} \frac{1}{\sqrt{2^n}} \sum_{m_T} |m_T\rangle (-1)^{(i_T \oplus j_T) \cdot m_T} |E_{i_I, i_T \oplus m_T, j_I, j_T \oplus m_T}\rangle \end{aligned}$$

Now, we can symmetrize information bits separately

$$|E_{i_I, j_I}^s\rangle = \frac{1}{\sqrt{2^n}} \sum_{m_I} |m_I\rangle (-1)^{(i_I \oplus j_I) \cdot m_I} |E_{i_I \oplus m_I, j_I \oplus m_I}^{s_T}\rangle \quad (18)$$

The above equation is used in Appendix D in that the attack still has 0/1 symmetry after the test bits are announced.

From Alice and Bob's prospective, Eve's attack has been averaged over all possible inputs. The probability of a given error is now independent of i :

$$\begin{aligned} P(|j\rangle = |i \oplus c\rangle)_{sym} &= \langle E_{i, i \oplus c}^s | E_{i, i \oplus c}^s \rangle \\ &= \frac{1}{2^{2n}} \sum_{m, m'} \langle E_{i \oplus m, i \oplus m \oplus c} | E_{i \oplus m', i \oplus m' \oplus c} \rangle \langle m | m' \rangle (-1)^{c \cdot (m \oplus m')} \\ &= \frac{1}{2^{2n}} \sum_m \langle E_{i \oplus m, i \oplus m \oplus c} | E_{i \oplus m, i \oplus m \oplus c} \rangle \\ &= \frac{1}{2^{2n}} \sum_{i'} \langle E_{i', i' \oplus c} | E_{i', i' \oplus c} \rangle \\ &= \frac{1}{2^{2n}} \sum_{i'} P(|j\rangle = |i' \oplus c\rangle)_{unsym} \end{aligned}$$

In the second to last step we change variables $i' = m \oplus i$.

The symmetrization makes the symmetrized error distribution equal to the averaged error distribution on the original attack. Hence the average error rate for Alice and Bob is the same for the two attacks. This is important as we assume that Eve loses nothing by applying a symmetric attack.

We have calculated the fact that the error does not depend on the sent bits for the information+test string. Similarly, the probabilities c_T and c_I are independent of Alice's choice of bits. This can be shown easily by modifying the above calculations in very straightforward ways to consider any choice of substring. Intuitively it is clear that if the whole error string has a probability distribution independent of i , then any randomly selected subsets would also.

D A Proof for Lemma 3.1

First we show that $\langle \phi_l | \phi_{l \oplus k} \rangle$ does not depend on l for a symmetrized attack:

From Appendix C we know that the symmetric attack after measurement can be written as:

$$|E_{i, j}\rangle = \frac{1}{\sqrt{2^n}} \sum_m (-1)^{(i \oplus j) \cdot m} |m\rangle |E_{i \oplus m, j \oplus m}^n\rangle$$

with $|E_{i,j}^n\rangle$ being the attack symmetrized only over test bits, after the Bob's test bits have been announced.

Now, we may compute $\langle\phi_l|\phi_{l\oplus k}\rangle$ for this (symmetric) attack:

$$\begin{aligned}\langle\phi_l|\phi_{l\oplus k}\rangle &= \sum_j \langle E_{l,j} | E_{l\oplus k, j\oplus k} \rangle \\ &= \frac{1}{2^n} \sum_{j,m} \langle E_{l\oplus m, j\oplus m}^n | E_{l\oplus m\oplus k, j\oplus m\oplus k}^n \rangle\end{aligned}$$

Change variables $m' = m \oplus l$ and $j' = j \oplus l$, so $j \oplus m = j' \oplus m'$

$$\langle\phi_l|\phi_{l\oplus k}\rangle = \frac{1}{2^n} \sum_{j',m'} \langle E_{m', j'\oplus m'}^n | E_{m'\oplus k, j'\oplus m'\oplus k}^n \rangle$$

Therefore, $\langle\phi_l|\phi_{l\oplus k}\rangle$ does not depend on l for the 0/1-symmetrized attacks. Thus, we can define $\langle\phi_l|\phi_{l\oplus k}\rangle = \Phi_k$.

Now, by definition of η , we have $\langle\eta_i|\eta_j\rangle = \frac{1}{2^{2n}} \sum_{l,m} (-1)^{l\cdot i} (-1)^{j\cdot m} \langle\phi_l|\phi_m\rangle$. Setting $k = l \oplus m$

$$\begin{aligned}\langle\eta_i|\eta_j\rangle &= \frac{1}{2^{2n}} \sum_{l,k} (-1)^{l\cdot i} (-1)^{j\cdot(l\oplus k)} \langle\phi_l|\phi_{l\oplus k}\rangle \\ &= \frac{1}{2^n} \sum_k (-1)^{j\cdot k} \Phi_k \left(\frac{1}{2^n} \sum_l (-1)^{l\cdot(i\oplus j)} \right) \\ &= \frac{1}{2^n} \sum_k (-1)^{j\cdot k} \Phi_k \delta_{i,j}\end{aligned}$$

When $i \neq j$, $\delta_{i,j}$ is zero, and thus

$$\langle\eta_i|\eta_j\rangle = 0. \tag{19}$$

QED

E A Proof for Lemma 3.2

First note that the norm of η_i satisfies

$$\begin{aligned}d_i^2 = \langle\eta_i|\eta_i\rangle &= \frac{1}{2^{2n}} \sum_l \sum_{l'} (-1)^{(l\oplus l')\cdot i} \langle\phi_l|\phi_{l'}\rangle = \\ &= \frac{1}{2^{2n}} \sum_l \sum_k (-1)^{i\cdot k} \langle\phi_l|\phi_{l\oplus k}\rangle \\ &= \frac{1}{2^{2n}} \sum_{l,k,j} (-1)^{i\cdot k} \langle E_{l,j} | E_{l\oplus k, j\oplus k} \rangle\end{aligned} \tag{20}$$

which was calculated using

$$\begin{aligned}\langle\phi_l|\phi_{l\oplus k}\rangle &= \sum_j \sum_{j'} \langle E_{l,j} | E_{l\oplus k, j'} \rangle \langle l \oplus j | l \oplus k \oplus j' \rangle \\ &= \sum_j \langle E_{l,j} | E_{l\oplus k, j\oplus k} \rangle\end{aligned}$$

After the test and the unused bits are announced we have:

$$|i\rangle \rightarrow \sum_j |E_{i,j}\rangle |j\rangle$$

The basis transformation is

$$|k\rangle^o = \frac{1}{\sqrt{2^n}} \sum_i (-1)^{i \cdot k} |i\rangle$$

Once Eve's attack is given in one basis it can be calculated in the other basis (due to linearity) so that:

$$|i\rangle^o \rightarrow \sum_j |E_{i,j}^o\rangle |j\rangle^o$$

with

$$|E_{k,l}^o\rangle = \frac{1}{2^n} \sum_{i,j} (-1)^{i \cdot k} (-1)^{j \cdot l} |E_{i,j}\rangle$$

For any given outcomes of the test and unused bits, the probability $P(c_I^o \mid i_T, j_T, b, s)$ of an error string c over the information bits in the opposite basis is

$$\begin{aligned} P(c_I^o \mid i_T, j_T, b, s) &= \frac{1}{2^n} \sum_k \langle E_{k,k \oplus c}^o | E_{k,k \oplus c}^o \rangle = \\ &= \frac{1}{2^n} \sum_k \sum_{i,j} \sum_{i',j'} \frac{1}{2^{2n}} (-1)^{(i \oplus i') \cdot k} (-1)^{(j \oplus j') \cdot (k \oplus c)} \langle E_{i,j} | E_{i',j'} \rangle \\ &= \frac{1}{2^{2n}} \sum_{i,j} \sum_{i',j'} \left(\frac{1}{2^n} \sum_k (-1)^{k \cdot (i \oplus i' \oplus j \oplus j')} \right) (-1)^{c \cdot (j \oplus j')} \langle E_{i,j} | E_{i',j'} \rangle \end{aligned}$$

The sum over k is non zero only when $i \oplus i' = j \oplus j' \triangleq h$

$$\begin{aligned} &= \frac{1}{2^{2n}} \sum_{i,j,h} (-1)^{c \cdot h} \langle E_{i,j} | E_{i \oplus h, j \oplus h} \rangle \\ &= \langle \eta_c | \eta_c \rangle = d_c^2 \end{aligned}$$

where the last equalities are due to the calculation of the norm of η in Eq. (20).

QED

F The Error Correction Code

After all the quantum bits are sent and Bob has made all his measurements, Alice announces an (n, k, d) ECC, $\mathcal{C}$, and the corresponding syndrome of her information bit string, i_I . In our protocol, $\mathcal{C}$, is announced by sending the $r = (n - k)$ rows $v_j, j = 1, \dots, r$ of a maximum rank $r \times n$ generator matrix, $\mathcal{H}$, of its dual code, $S_s = \mathcal{C}^\perp = \{v_s \in \{0, 1\}^n \mid v_s \cdot c = 0 \ \forall c \in \mathcal{C}\}$ [and $\{v_1, \dots, v_r\}$ is a basis of $S_s = \mathcal{C}^\perp$]. The code-syndrome sent by Alice comprises $\xi^{Alice} \equiv \mathcal{H} \cdot i_I$. Bob can now calculate $\xi^{Bob} \equiv \mathcal{H} \cdot j_I$. Since $j_I = i_I \oplus c_I$, he can learn $\mathcal{H} \cdot c_I = \xi^{Alice} \oplus \xi^{Bob}$. Hence, Bob has the syndrome of his error string and can correct the errors if $|c_I| \leq (d - 1)/2$.

In the case of a one bit key, the final key is extracted as $b = i_I \cdot v$, where $v \in \{0, 1\}^n$ is the string defined for PA. Of course v is chosen such that $v \notin S_s$. Before we proceed, we shall choose once and for all a subspace S_s^c of $\{0, 1\}^n$ containing v and such that S_s and S_s^c are complementary; this means that S_s^c is an $(n - r)$ dimensional subspace, such that $S_s^c \oplus S_s = \{0, 1\}^n$, and $S_s^c \cap S_s = \{0\}$. Of course $S_s^c \neq S_s^\perp = \mathcal{C}$. Note that S_s^c is not unique (but is easy to construct after augmenting the set of vectors $\{v_1, \dots, v_r, v\}$ to a basis of $\{0, 1\}^n$).

The preceding error correction procedure, however, provides additional information to Eve. In particular, since Eve knows $\mathcal{H}$ (i.e., the generator matrix of S_s) and the syndrome $\xi^{Alice} \equiv \mathcal{H} \cdot i_I$, Eve knows which coset $\mathcal{C}_\xi = \{i_I \in \{0, 1\}^n \mid \mathcal{H} i_I = \xi\}$ of $\mathcal{C}$ Alice's information bit string, i_I , belongs to. That is, she learns it belongs to $\mathcal{C}_\xi$ for $\xi = \xi^{Alice}$.

Let i_ξ denote a code word in the coset $\mathcal{C}_\xi$ (we dropped the index I , for convenience). Note that for any $i_\xi \in \mathcal{C}_\xi$ we have

$$\mathcal{C}_\xi = \{(i_\xi \oplus c \mid c \in \mathcal{C}),$$

that is, all other code words in the coset $\mathcal{C}_\xi$ can be obtained from one code word in $\mathcal{C}_\xi$ by calculating its exclusive-or with all the code words in the original linear code $\mathcal{C}$. We now choose arbitrarily an i_ξ in each $\mathcal{C}_\xi$. Those arbitrary¹ but fixed strings will often be referred to in the next appendix.

G Eve's Information Versus the disturbance

In this appendix we do not prove Lemma 3.3 immediately. We prove it later on, in the second subsection (the tight bound). For simplicity of the presentation, we first prove another Lemma which leads to a loose bound (with an additional factor of 2^r), for which the derivation is simpler. The bulk of the loose bound was derived in [3], and the tight bound is an improvement over that derivation. The loose bound lead to a much worse threshold for p_{allowed} (less than 1%, instead of 7.56% derived from the tight bound), and this is the motivation for deriving the tight bound. One can skip directly to the second subsection if desired.

Both the loose and the tight bound are derived using the fact that the Shannon distinguishability between the parity 0 density matrix, ρ_0 , and the parity 1 density matrix, ρ_1 , is bounded by the trace norm of $\rho_0 - \rho_1$, and using the fact that the one can easily calculate this trace-norm when the purified states are given by Eq. 4.

G.1 The Loose Bound (BBBGM)

We have already defined a purification of Eve's state: $|\phi_{i_I}\rangle = \sum_l (-1)^{i_I \cdot l} |\eta_l\rangle$. The density matrix for such a $|\phi_{i_I}\rangle$ is

$$\rho^{i_I} = |\phi_{i_I}\rangle\langle\phi_{i_I}| = \sum_{l,l'} (-1)^{i_I(l \oplus l')} d_l d_{l'} |\hat{\eta}_l\rangle\langle\hat{\eta}_{l'}| \quad (21)$$

Recall that the final key is computed as $v \cdot i_I$. Eve does not know i_I , but she knows from the announced syndrome that i_I is in the coset $\mathcal{C}_\xi$ for $\xi \equiv \xi^{\text{Alice}}$. Hence, in order to know the key, Eve must distinguish between the states $i_I = i_\xi \oplus c$ in $\mathcal{C}_\xi$ that give parity zero and the states $i_I = i_\xi \oplus c$ in $\mathcal{C}_\xi$ that give parity one. For $b \in \{0, 1\}$ the reduced density matrix is

$$\begin{aligned} \rho_b &= \frac{1}{2^{n-(r+1)}} \sum_{\substack{c \in \mathcal{C} \\ v(i_\xi \oplus c) = b}} \rho^{i_\xi \oplus c} = \\ &= \frac{1}{2^{n-(r+1)}} \sum_{\substack{c \in \mathcal{C} \\ v(i_\xi \oplus c) = b}} \sum_{l,l'} (-1)^{(i_\xi \oplus c)(l \oplus l')} d_l d_{l'} |\hat{\eta}_l\rangle\langle\hat{\eta}_{l'}| \end{aligned}$$

where the sum is over c that satisfy both the condition of being a code word, and the condition of leading to the particular parity b for the PA.

Lemma. Let $\mathcal{C}$ be any linear code in $\{0, 1\}^n$ and $a \in \{0, 1\}^n$ be such that $a \notin \mathcal{C}^\perp$ then

$$\sum_{c \in \mathcal{C}} (-1)^{c \cdot a} = 0 \quad (22)$$

Proof.— Let $\{w_1, \dots, w_k\}$ be a basis of $\mathcal{C}$. Define $t \in \{0, 1\}^k$ by $t_\alpha = w_\alpha \cdot a$, $1 \leq \alpha \leq k$; $a \notin \mathcal{C}^\perp$ means that t is not the zero string. Let now $h : \{0, 1\}^k \rightarrow \mathcal{C}$ be defined by $h(s) = \sum_{1 \leq \alpha \leq k} s_\alpha w_\alpha$; then $h(s) \cdot a = \sum s_\alpha w_\alpha \cdot a = \sum s_\alpha t_\alpha = s \cdot t$ and so

$$\sum_{c \in \mathcal{C}} (-1)^{c \cdot a} = \sum_s (-1)^{h(s) \cdot a} = \sum_s (-1)^{s \cdot t} = 0$$

¹In fact there is a unique $i_\xi \in (S_\mathbf{s}^c)^\perp \cap \mathcal{C}_\xi$ but that is irrelevant for our proofs.

Lemma The Shannon distinguishability between the parity 0 and the parity 1 of the information bits over any PA string, v , is bounded above by the following inequality:

$$SD_v \leq 2^r \left[\alpha + \frac{1}{\alpha} \sum_{|l| \geq \frac{\hat{v}}{2}} d_l^2 \right], \quad (23)$$

where $\hat{v}$ is the minimum weight of $v \oplus v_s$ for any $v_s \in S_s$, and α is any positive constant.

Proof.— The Shannon distinguishability between the parity 0 and the parity 1 is bounded by the trace norm of $\rho_0 - \rho_1$ ([3, 20]). Let us calculate the required bound:

$$\begin{aligned} \rho_0 - \rho_1 &= \frac{1}{2^{n-(r+1)}} \sum_{c \in \mathcal{C}} (-1)^{(i_\xi \oplus c)v} \sum_{l, l'} (-1)^{(i_\xi \oplus c)(l \oplus l')} d_l d_{l'} |\hat{\eta}_l\rangle \langle \hat{\eta}_{l'}| \\ &= \frac{1}{2^{n-(r+1)}} \sum_{l, l'} \left(\sum_{c \in \mathcal{C}} (-1)^{(i_\xi \oplus c)(l \oplus l' \oplus v)} \right) d_l d_{l'} |\hat{\eta}_l\rangle \langle \hat{\eta}_{l'}| \\ &= \frac{1}{2^{n-(r+1)}} \sum_{l, l'} (-1)^{i_\xi(l \oplus l' \oplus v)} \left(\sum_{c \in \mathcal{C}} (-1)^{c(l \oplus l' \oplus v)} \right) d_l d_{l'} |\hat{\eta}_l\rangle \langle \hat{\eta}_{l'}| \end{aligned}$$

From equation (22) we know the sum over $\mathcal{C}$ is zero except when $l \oplus l' \oplus v \in \mathcal{C}^\perp = S_s$, i.e. when $l' = l \oplus v \oplus v_s$ for some $v_s \in S_s$. As a consequence:

$$\rho_0 - \rho_1 = 2 \sum_{v_s \in S_s} (-1)^{i_\xi \cdot v_s} \sum_l d_l d_{l \oplus v \oplus v_s} |\hat{\eta}_l\rangle \langle \hat{\eta}_{l \oplus v \oplus v_s}|$$

The trace norm of this matrix serves as a bound on the information Eve receives.

$$SD_v \leq \frac{1}{2} \text{Tr} |\rho_0 - \rho_1|$$

Using the above and making use of the triangle inequality for the Trace norm, the following is obtained:

$$\begin{aligned} SD_v &\leq \text{Tr} \left| \sum_{v_s \in S_s} (-1)^{i_\xi \cdot v_s} \sum_l d_l d_{l \oplus v \oplus v_s} |\hat{\eta}_l\rangle \langle \hat{\eta}_{l \oplus v \oplus v_s}| \right| \\ &= \frac{1}{2} \text{Tr} \left| \sum_{v_s \in S_s} (-1)^{i_\xi \cdot v_s} \sum_l d_l d_{l \oplus v \oplus v_s} (|\hat{\eta}_l\rangle \langle \hat{\eta}_{l \oplus v \oplus v_s}| + |\hat{\eta}_{l \oplus v \oplus v_s}\rangle \langle \hat{\eta}_l|) \right| \\ &\leq \sum_{v_s \in S_s} \sum_l d_l d_{l \oplus v \oplus v_s} \left(\frac{1}{2} \text{Tr} (|\hat{\eta}_l\rangle \langle \hat{\eta}_{l \oplus v \oplus v_s}| + |\hat{\eta}_{l \oplus v \oplus v_s}\rangle \langle \hat{\eta}_l|) \right) \\ &= \sum_{v_s \in S_s} \sum_l d_l d_{l \oplus v \oplus v_s} \end{aligned}$$

Now we will concern ourselves with bounding each of the terms $\sum_l d_l d_{l \oplus w_s}$, where $w_s = v \oplus v_s$.

$$\begin{aligned} \sum_l d_l d_{l \oplus w_s} &= \sum_{|l| > \frac{|w_s|}{2}} d_l d_{l \oplus w_s} + \sum_{|l| \leq \frac{|w_s|}{2}} d_l d_{l \oplus w_s} \\ &= \sum_{|l| > \frac{|w_s|}{2}} d_l d_{l \oplus w_s} + \sum_{|l' \oplus w_s| \leq \frac{|w_s|}{2}} d_{l' \oplus w_s} d_{l'} \end{aligned}$$

If $|l' \oplus w_s| \leq \frac{|w_s|}{2}$ then $|w_s| = |l' \oplus w_s \oplus l'| \leq |l' \oplus w_s| + |l'| \leq \frac{|w_s|}{2} + |l'|$ and so $|l'| \geq \frac{|w_s|}{2}$. Therefore,

$$\begin{aligned}
\sum_{|l| > \frac{|w_s|}{2}} d_l d_{l \oplus w_s} + \sum_{|l' \oplus w_s| \leq \frac{|w_s|}{2}} d_{l' \oplus w_s} d_{l'} &\leq \sum_{|l| \geq \frac{|w_s|}{2}} d_l d_{l \oplus w_s} + \sum_{|l'| \geq \frac{|w_s|}{2}} d_{l' \oplus w_s} d_{l'} \\
&= 2 \sum_{|l| \geq \frac{|w_s|}{2}} d_l d_{l \oplus w_s} \\
&= \frac{1}{\alpha} \sum_{|l| \geq \frac{|w_s|}{2}} 2d_l (\alpha d_{l \oplus w_s}) \\
&\leq \frac{1}{\alpha} \sum_{|l| \geq \frac{|w_s|}{2}} [d_l^2 + \alpha^2 d_{l \oplus w_s}^2] \\
&= \alpha \sum_{|l| \geq \frac{|w_s|}{2}} d_{l \oplus w_s}^2 + \frac{1}{\alpha} \sum_{|l| \geq \frac{|w_s|}{2}} d_l^2
\end{aligned}$$

where the last three steps are true for any real α , and real $d_l, d_{l \oplus w_s}$.

Due to the fact that the d_l^2 form a probability distribution, any sum of them is less than or equal to unity.

$$\begin{aligned}
\sum_l d_l d_{l \oplus w_s} &\leq \alpha + \frac{1}{\alpha} \sum_{|l| \geq \frac{|w_s|}{2}} d_l^2 \\
&\leq \alpha + \frac{1}{\alpha} \sum_{|l| \geq \frac{\hat{v}}{2}} d_l^2
\end{aligned}$$

where $\hat{v} = \min_{v_s} |v \oplus v_s|$ (remember that $w_s = v \oplus v_s$). Summing over all $v_s \in S_s$ now leaves:

$$SD_v \leq 2^r \left[\alpha + \frac{1}{\alpha} \sum_{|l| \geq \frac{\hat{v}}{2}} d_l^2 \right] \quad (24)$$

QED

The BBBGM result gives an upper bound for Eve's information about the bit defined by this privacy amplification string v . To prove security in case of m bits in the final key, we prove security of each bit as follows: for each bit in the key we assume that Eve is given the ECC information and in addition, she is also given all the other bits in the key. This is like using a code with more parity check strings 2^{r+m-1} (or less code words), hence the previous result holds with

$$SD_v \leq 2^{r+m-1} \left[\alpha + \frac{1}{\alpha} \sum_{|l| \geq \frac{\hat{v}}{2}} d_l^2 \right]. \quad (25)$$

Following the proof of the above Lemma, one can see that it is not a tight bound since we sum over 2^r terms while most of them are much smaller than the term (terms) with the minimal $\hat{v}$.

G.2 Eve's Information on one bit – Tight Bound

We now show an improved technique, by defining a basis for the purification of the code words (instead of a basis for all the purification).

We will now make a finer analysis of Eve's state after she learns the parity matrix and the syndrome $\xi = \xi^{Alice}$. We start again from the equality:

$$|\phi_{i_I}\rangle = \sum_l (-1)^{i_I \cdot l} |\eta_l\rangle \quad (26)$$

First, any $l \in \{0, 1\}^n$ has a unique representation $l = m \oplus n$ with $m \in S_s^c$ and $n \in S_s$. Next, for any $i_I \in \mathcal{C}_\xi$ we have $i_I = i_\xi \oplus c$ for some $c \in \mathcal{C}$ and thus for any $n \in S_s$ we get $i_I \cdot n = (i_\xi \oplus c) \cdot n = i_\xi \cdot n$ [because $n \in S_s = \mathcal{C}^\perp$]. Putting those two remarks together we get:

$$\begin{aligned} |\phi_{i_I}\rangle &= \sum_{m \in S_s^c} \sum_{n \in S_s} (-1)^{i_I \cdot (m \oplus n)} |\eta_{m \oplus n}\rangle \\ &= \sum_{m \in S_s^c} (-1)^{i_I \cdot m} \sum_{n \in S_s} (-1)^{i_I \cdot n} |\eta_{m \oplus n}\rangle \\ &= \sum_{m \in S_s^c} (-1)^{i_I \cdot m} \sum_{n \in S_s} (-1)^{i_\xi \cdot n} |\eta_{m \oplus n}\rangle \\ &= \sum_{m \in S_s^c} (-1)^{i_I \cdot m} |\eta'_m\rangle \end{aligned}$$

where η'_m is of course defined for each $m \in S_s$ by

$$|\eta'_m\rangle = \sum_{n \in S_s} (-1)^{i_\xi \cdot n} |\eta_{m \oplus n}\rangle \quad (27)$$

Now, since $\langle \eta_{m_1 \oplus n_1} | \eta_{m_2 \oplus n_2} \rangle = 0$ except when $m_1 \oplus n_1 = m_2 \oplus n_2$, which implies $m_1 = m_2$, the η_m 's are orthogonal. If d'_m is the length of η'_m , we can then write

$$\eta'_m = d'_m \hat{\eta}'_m$$

with the $\hat{\eta}'_m$'s normalized and orthogonal and

$$d'^2_m = \sum_{n \in S_s} d'^2_{m \oplus n}$$

and the density matrix for $|\phi_{i_I}\rangle$ reduces to:

$$\begin{aligned} \rho^{i_I} &= |\phi_{i_I}\rangle \langle \phi_{i_I}| = \\ &= \sum_{m, m' \in S_s^c} (-1)^{i_I \cdot (m \oplus m')} d'_m d'_{m'} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m'}| \end{aligned}$$

Recall that the final key is computed as $b = v \cdot i_I$. Of course, Eve does not know i_I , but she knows from the announced syndrome $\xi = \xi^{Alice}$ that $i_I \in \mathcal{C}_\xi = \{i_\xi \oplus c \mid c \in \mathcal{C}\}$ and wants to determine b . For $b \in \{0, 1\}$ the reduced density matrix is

$$\begin{aligned} \rho_b &= \frac{1}{2^{n-(r+1)}} \sum_{\substack{c \in \mathcal{C} \\ (i_\xi \oplus c)v=b}} \rho^{i_\xi \oplus c} = \\ &= \frac{1}{2^{n-(r+1)}} \sum_{\substack{c \in \mathcal{C} \\ (i_\xi \oplus c)v=b}} \sum_{m, m' \in S_s^c} (-1)^{(i_\xi \oplus c) \cdot (m \oplus m')} d'_m d'_{m'} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m'}| \end{aligned}$$

Lemma G.1 3.3 The Shannon distinguishability between the parity 0 and the parity 1 of the information bits over any PA string, v , is bounded above by the following inequality:

$$SD_v \leq \alpha + \frac{1}{\alpha} \sum_{|l| \geq \frac{\hat{v}}{2}} d_l^2, \quad (28)$$

where $\hat{v}$ is the minimum weight of $v \oplus v_s$ for any $v_s \in S_s$, and α is any positive constant.

Proof: The Shannon distinguishability between the parity 0 and the parity 1 is bounded by the trace norm of $\rho_0 - \rho_1$:

$$\begin{aligned} \rho_0 - \rho_1 &= \frac{1}{2^{n-(r+1)}} \sum_{c \in \mathcal{C}} (-1)^{(i_\xi \oplus c)v} \sum_{m, m' \in S_s^c} (-1)^{(i_\xi \oplus c)(m \oplus m')} d'_m d'_{m'} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m'}| \\ &= \frac{1}{2^{n-(r+1)}} \sum_{m, m' \in S_s^c} \left(\sum_{c \in \mathcal{C}} (-1)^{(i_\xi \oplus c)(m \oplus m' \oplus v)} \right) d'_m d'_{m'} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m'}| \\ &= \frac{1}{2^{n-(r+1)}} \sum_{m, m' \in S_s^c} (-1)^{i_\xi(m \oplus m' \oplus v)} \left(\sum_{c \in \mathcal{C}} (-1)^{c \cdot (m \oplus m' \oplus v)} \right) d'_m d'_{m'} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m'}| \end{aligned}$$

Applying equality (22) the sum indexed by c is zero except when $m \oplus m' \oplus v \in \mathcal{C}^\perp = S_s$. But $m \oplus m' \oplus v \in S_s^c$ because m, m' and $v \in S_s^c$. This implies $m \oplus m' \oplus v \in S_s \cap S_s^c = \{0\}$ and thus $m' = m \oplus v$. Of course, with $m \oplus m' \oplus v = 0$, the sum indexed by c is $2^k = 2^{n-r}$ and the coefficient $(-1)^{i_\xi(m \oplus m' \oplus v)}$ is 1. Therefore $\rho_0 - \rho_1$ takes the very simple form:

$$\rho_0 - \rho_1 = 2 \sum_{m \in S_s^c} d'_m d'_{m \oplus v} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m \oplus v}|$$

As usual, the trace norm of this matrix serves as a bound on the information Eve receives. It is

$$SD_v \leq \frac{1}{2} \text{Tr} |\rho_0 - \rho_1|$$

First note that v is in S_s^c and S_s^c is closed under addition. Further the set S_s^c is the same as $v \oplus S_s^c$. Then the set defined by $m \in S_s^c$ is identical to the set $m \oplus v \in S_s^c$. We will use this identity to obtain the following inequality:

$$\begin{aligned} SD_v &\leq \text{Tr} \left| \sum_{m \in S_s^c} d'_m d'_{m \oplus v} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m \oplus v}| \right| \\ &= \frac{1}{2} \text{Tr} \left| \sum_{m \in S_s^c} d'_m d'_{m \oplus v} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m \oplus v}| + \sum_{m \oplus v \in S_s^c} d'_m d'_{m \oplus v} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m \oplus v}| \right| \\ &= \frac{1}{2} \text{Tr} \left| \sum_{m \in S_s^c} d'_m d'_{m \oplus v} |\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m \oplus v}| + \sum_{m \in S_s^c} d'_{m \oplus v} d'_m |\hat{\eta}'_{m \oplus v}\rangle \langle \hat{\eta}'_m| \right| \\ &= \frac{1}{2} \text{Tr} \left| \sum_{m \in S_s^c} d'_m d'_{m \oplus v} (|\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m \oplus v}| + |\hat{\eta}'_{m \oplus v}\rangle \langle \hat{\eta}'_m|) \right| \\ &\leq \frac{1}{2} \sum_{m \in S_s^c} d'_m d'_{m \oplus v} \text{Tr} ||\hat{\eta}'_m\rangle \langle \hat{\eta}'_{m \oplus v}| + |\hat{\eta}'_{m \oplus v}\rangle \langle \hat{\eta}'_m|| \\ &= \sum_{m \in S_s^c} d'_m d'_{m \oplus v} \end{aligned}$$

Now we wish to give a bound in terms of the original d 's. Let us define

$$\Gamma_{\hat{v}} = \{m \in S_{\mathbf{s}}^c \mid |m \oplus n| \geq \hat{v}/2 \ \forall n \in S_{\mathbf{s}}\}$$

where $\hat{v}$ was defined in the statement of the lemma. We claim that for any $m \in S_{\mathbf{s}}^c$, either $m \in \Gamma_{\hat{v}}$ or $m \oplus v \in \Gamma_{\hat{v}}$. Indeed, if it were not so, there would be $n_1 \in S_{\mathbf{s}}$ and $n_2 \in S_{\mathbf{s}}$ such that $|m \oplus n_1| < \hat{v}/2$ and $|m \oplus v \oplus n_2| < \hat{v}/2$. But then $|n_1 \oplus n_2 \oplus v| = |m \oplus n_1 \oplus m \oplus n_2 \oplus v| < \hat{v}/2 + \hat{v}/2$ which, since $n_1 \oplus n_2 \in S_{\mathbf{s}}$, contradicts the definition of $\hat{v}$.

We now use the claim to break up the sum bounding SD_v and prove the lemma.

$$\begin{aligned} SD_v &\leq \sum_{m \in S_{\mathbf{s}}^c} d'_m d'_{m \oplus v} \\ &\leq \left(\sum_{\substack{m \in S_{\mathbf{s}}^c \\ m \in \Gamma_{\hat{v}}}} d'_m d'_{m \oplus v} + \sum_{\substack{m \in S_{\mathbf{s}}^c \\ m \oplus v \in \Gamma_{\hat{v}}}} d'_m d'_{m \oplus v} \right) \\ &= \left(\sum_{\substack{m \in S_{\mathbf{s}}^c \\ m \in \Gamma_{\hat{v}}}} d'_m d'_{m \oplus v} + \sum_{\substack{m \oplus v \in S_{\mathbf{s}}^c \\ m \in \Gamma_{\hat{v}}}} d'_m d'_{m \oplus v} \right) \\ &= 2 \sum_{m \in \Gamma_{\hat{v}}} d'_m d'_{m \oplus v} \\ &= \frac{2}{\alpha} \sum_{m \in \Gamma_{\hat{v}}} (\alpha d'_{m \oplus v})(d'_m) \\ &\leq \alpha \sum_{m \in \Gamma_{\hat{v}}} d_{m \oplus v}^2 + \frac{1}{\alpha} \sum_{m \in \Gamma_{\hat{v}}} d_m^2 \\ &\leq \alpha \sum_{\substack{m \in S_{\mathbf{s}}^c, n \in S_{\mathbf{s}} \\ |m \oplus n| \geq \frac{\hat{v}}{2}}} d_{m \oplus n}^2 + \frac{1}{\alpha} \sum_{\substack{m \in S_{\mathbf{s}}^c, n \in S_{\mathbf{s}} \\ |m \oplus n| \geq \frac{\hat{v}}{2}}} d_{m \oplus n}^2 \\ &= \alpha \sum_{|l| \geq \frac{\hat{v}}{2}} d_{l \oplus v}^2 + \frac{1}{\alpha} \sum_{|l| \geq \frac{\hat{v}}{2}} d_l^2 \end{aligned}$$

Due to the fact that the d_l^2 form a probability distribution, any sum of them is less than or equal to unity.

$$SD_v \leq \alpha + \frac{1}{\alpha} \sum_{|l| \geq \frac{\hat{v}}{2}} d_l^2 \quad (29)$$

QED

Note that the number of parity check strings r doesn't appear in the final expression, and this might seem surprising. However, it does appear there implicitly, since increasing r by one increases the number of parity check strings from $2^r - 1$ to $2^{r+1} - 1$, hence potentially decreases $\hat{v}$.

H Security of the Entire Key

We give a proof that bitwise security implies security of the entire string. This is first shown classically, and then making use of Shannon Distinguishability, the same bound holds for quantum bits.

H.1 Classical Information Theory

Lemma H.1 For independent random variables $\mathcal{A}_i$, $i \in (1, 2, \dots, m)$ and random variable $\mathcal{E}$
 $I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_{i-1}) \leq I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_{i-1}, \mathcal{A}_{i+1}, \dots, \mathcal{A}_m)$

Proof: First we define a few sets: $\mathcal{A}_{<i} \equiv \{\mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_{i-1}\}$, $\mathcal{A}_{>i} \equiv \{\mathcal{A}_{i+1}, \mathcal{A}_{i+2}, \dots, \mathcal{A}_m\}$, and $\mathcal{A}_{\neq i} \equiv \{\mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_{i-1}, \mathcal{A}_{i+1}, \dots, \mathcal{A}_m\}$. Of course, $\mathcal{A}_{\neq i} = \mathcal{A}_{<i} \cup \mathcal{A}_{>i}$. In this notation the lemma says: $I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i}) - I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{<i}) \geq 0$

$$\begin{aligned}
 I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i}) - I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{<i}) &= H(\mathcal{A}_i | \mathcal{A}_{\neq i}) - H(\mathcal{A}_i | \mathcal{E}, \mathcal{A}_{\neq i}) - H(\mathcal{A}_i | \mathcal{A}_{<i}) + H(\mathcal{A}_i | \mathcal{E}, \mathcal{A}_{<i}) \\
 &= (H(\mathcal{A}_i | \mathcal{E}, \mathcal{A}_{<i}) - H(\mathcal{A}_i | \mathcal{E}, \mathcal{A}_{\neq i})) - (H(\mathcal{A}_i | \mathcal{A}_{<i}) - H(\mathcal{A}_i | \mathcal{A}_{\neq i})) \\
 &= (H(\mathcal{A}_i | \mathcal{E}, \mathcal{A}_{<i}) - H(\mathcal{A}_i | \mathcal{E}, \mathcal{A}_{<i}, \mathcal{A}_{>i})) \\
 &\quad - (H(\mathcal{A}_i | \mathcal{A}_{<i}) - H(\mathcal{A}_i | \mathcal{A}_{<i}, \mathcal{A}_{>i})) \\
 &= I(\mathcal{A}_i; \mathcal{A}_{>i} | \mathcal{E}, \mathcal{A}_{<i}) - I(\mathcal{A}_i; \mathcal{A}_{>i} | \mathcal{A}_{<i})
 \end{aligned}$$

Due to the independence of $\mathcal{A}_i$, $I(\mathcal{A}_i; \mathcal{A}_{>i} | \mathcal{A}_{<i}) = 0$. Since any information is non-negative, $I(\mathcal{A}_i; \mathcal{A}_{>i} | \mathcal{E}, \mathcal{A}_{<i}) \geq 0$. Hence $I(\mathcal{A}_i; \mathcal{A}_{>i} | \mathcal{E}, \mathcal{A}_{<i}) - I(\mathcal{A}_i; \mathcal{A}_{>i} | \mathcal{A}_{<i}) \geq 0$ **QED**

Theorem H.1 For independent random variables $\mathcal{A}_i$, $i \in (1, 2, \dots, m)$ and random variable $\mathcal{E}$
 $I(\mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_m; \mathcal{E}) \leq m \max_i (I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_{i-1}, \mathcal{A}_{i+1}, \dots, \mathcal{A}_m))$

Proof: Here we simply apply the chain rule for mutual information[21] and we then apply the above lemma. We will use the same notions introduced in the previous proof.

$$\begin{aligned}
 I(\mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_m; \mathcal{E}) &= \sum_i I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{<i}) \\
 &\leq \sum_k I(\mathcal{A}_k; \mathcal{E} | \mathcal{A}_{\neq k}) \\
 &\leq \sum_k \max_i (I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i})) \\
 &= m \max_i (I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i}))
 \end{aligned}$$

QED

Lemma H.2 For independent random variables $\mathcal{A}_i$, $i \in (1, 2, \dots, m)$ and random variable $\mathcal{E}$
 $I(\mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_m; \mathcal{E}) \leq m \max_{i, a_{\neq i}} (I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i} = a_{\neq i}))$. Where $a_{\neq i}$ is a set of outcomes for all $\mathcal{A}$ except i .

Proof: We must simply prove $I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i}) \leq \max_{a_{\neq i}} I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i} = a_{\neq i})$ and then apply the previous theorem.

$$\begin{aligned}
 I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i}) &= \sum_{a_{\neq i}} P(\mathcal{A}_{\neq i} = a_{\neq i}) I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i} = a_{\neq i}) \\
 &\leq \sum_{a_{\neq i}} P(\mathcal{A}_{\neq i} = a_{\neq i}) \max_{a'_{\neq i}} I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i} = a'_{\neq i}) \\
 &= \max_{a_{\neq i}} I(\mathcal{A}_i; \mathcal{E} | \mathcal{A}_{\neq i} = a_{\neq i})
 \end{aligned}$$

QED

H.2 Quantum Connection

We have used classical information theory to prove the above identities. In the quantum setting, Eve has a quantum system that may depend on Alice's bits, $\mathcal{A}_i$. The classical formulas are all valid once a particular measurement on the system (POVM) is fixed by Eve, so that:

$$I(\mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_m; \mathcal{E}^M) \leq m \max_{i, a_{\neq i}} I(\mathcal{A}_i; \mathcal{E}^M | \mathcal{A}_{\neq i} = a_{\neq i}) \quad (30)$$

where $\mathcal{E}^M$ is the random variable obtained by Eve's output from her measurement M . In particular the above is true for any measurement, $\tilde{M}$, that Eve may consider optimal to learn the bits of Alice's key, $\mathcal{A}_i$, all at once.

Now we need the definition of Shannon Distinguishability:

$$SD^{i, a_{\neq i}} \equiv \sup_M I(\mathcal{A}_i; \mathcal{E}^M | \mathcal{A}_{\neq i} = a_{\neq i}) \quad (31)$$

Note, a measurement that achieves (or nearly achieves) this upper bound may not be optimal for eavesdropping on the entire key, but that is of no consequence to the proof. Therefore, $I(\mathcal{A}_i; \mathcal{E}^M | \mathcal{A}_{\neq i} = a_{\neq i}) \leq SD^{i, a_{\neq i}}$ for all M and in particular

$$I(\mathcal{A}_i; \mathcal{E}^{\tilde{M}} | \mathcal{A}_{\neq i} = a_{\neq i}) \leq SD^{i, a_{\neq i}} \quad (32)$$

Hence we have a bound for total mutual information for any measurement Eve might consider optimal:

$$I(\mathcal{A}_1, \mathcal{A}_2, \dots, \mathcal{A}_m; \mathcal{E}^{\tilde{M}}) \leq m \max_{i, a_{\neq i}} SD^{i, a_{\neq i}} \quad (33)$$

I A Proof of Lemma 4.1

To prove this lemma we first note that $P(c_T, i_T, \mathcal{T} = \text{pass} | b, s) = P(c_T, i_T | b, s)$ when we sum only over such terms c_T that pass the test. Then we apply equation 8:

$$I(\mathcal{A}; \mathcal{E} | i_T, j_T, b, s) \leq m \left[\alpha + \frac{1}{\alpha} \sum_{|c_I| \geq \frac{\hat{v}}{2}} P(c_I^o | i_T, j_T, b, s) \right]$$

Thus:

$$\begin{aligned} \sum_{i_T, c_T} P(\mathcal{T} = \text{pass}, i_T, c_T | b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) &= \sum_{\frac{|c_T|}{n} \leq p_{\text{allowed}}} \sum_{i_T} P(i_T, c_T | b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \\ &\leq m \left(\alpha \sum_{\frac{|c_T|}{n} \leq p_{\text{allowed}}} \sum_{i_T} P(i_T, c_T | b, s) + \frac{1}{\alpha} \sum_{\frac{|c_T|}{n} \leq p_{\text{allowed}}} \sum_{i_T} P(i_T, c_T | b, s) \sum_{|c_I| > \frac{\hat{v}}{2}} P(c_I^o | c_T, i_T, b, s) \right) \\ &= m \left(\alpha P(\mathcal{T} = \text{pass} | b, s) + \frac{1}{\alpha} \sum_{\frac{|c_T|}{n} \leq p_{\text{allowed}}} \sum_{|c_I| > \frac{\hat{v}}{2}} \sum_{i_T} P(c_I^o, c_T, i_T | b, s) \right) \\ &= m \left(\alpha P(\mathcal{T} = \text{pass} | b, s) + \frac{1}{\alpha} \sum_{\frac{|c_T|}{n} \leq p_{\text{allowed}}} \sum_{|c_I| > \frac{\hat{v}}{2}} P(c_I^o, c_T | b, s) \right) \end{aligned}$$

The dependence on the i_T has been removed by averaging over all values. Since, the probability of passing the test, $P(\mathcal{T} = \text{pass} | b, s)$ is less than unity we replace it by 1. Also,

$\sum_{\frac{|c_T|}{n} \leq p_{\text{allowed}}} \sum_{|c_I| > \frac{\hat{v}}{2}} P(c_I^o, c_T | b, s) \equiv P[(\frac{|C_I^o|}{n} > \frac{\hat{v}}{2}) \cap (\frac{|C_T|}{n} \leq p_{\text{allowed}}) | b, s]$ Thus,

$$\sum_{i_T, c_T} P(\mathcal{T} = \text{pass}, i_T, c_T | b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq m \left(\alpha + \frac{1}{\alpha} P[(\frac{|C_I^o|}{n} > \frac{\hat{v}}{2}) \cap (\frac{|C_T|}{n} \leq p_{\text{allowed}}) | b, s] \right)$$

J A Proof of Lemma 4.2

Here we show that:

$$\sum_b P\left(\left(\frac{|C_I^o|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b, s\right) = \sum_b P\left(\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b, s\right) \quad (34)$$

There are 2^{2n} possible basis strings that Alice is equally likely to choose. Therefore $P(b) = \frac{1}{2^{2n}}$. Combining the above with the average over b of lemma 4.1 we get the desired result:

$$\sum_{i_T, c_T, b} P(\mathcal{T} = \text{pass}, i_T, c_T, b | s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq \alpha + \frac{1}{\alpha} \frac{1}{2^{2n}} \sum_b P\left[\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b, s\right] \quad (35)$$

We have assumed a particular basis string b was announced, and that a bit-selection string s was announced. For a fixed bit-selection s and bases b we define the unique strings b_I and b_T which are two substrings of b where one contains only the bases of the information bits, and the other only the bases of the test bits, while the internal order (inside b_I and b_T is as the internal order in b . For instance, if $s = 111100001100$, and $b = 010100110101$ then $b_I = 001101$ and $b_T = 010101$.

Recall that C_I^o is the error string had the *opposite* basis been used for the information bits. Thus we can equivalently write:

$$P\left(\left(\frac{|C_I^o|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b_I, b_T, s\right) \equiv P\left(\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | \bar{b}_I, b_T, s\right)$$

Averaging over all bases of the information bits b_I we get

$$\sum_{b_I} P\left(\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | \bar{b}_I, b_T, s\right) = \sum_{b_I} P\left(\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b_I, b_T, s\right),$$

Now we can also sum over the bases of the test bits to get

$$\sum_{b_I, b_T} P\left(\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | \bar{b}_I, b_T, s\right) = \sum_{b_I, b_T} P\left(\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b_I, b_T, s\right),$$

so that

$$\sum_{i_T, c_T, b} P(\mathcal{T} = \text{pass}, i_T, c_T, b | s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq \alpha + \frac{1}{\alpha} \frac{1}{2^{2n}} \sum_b P\left[\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b, s\right] \quad (36)$$

Note that in the above equation the dependence on b in the right hand side has been removed by averaging. This is just the average over all choices of basis.

K A Proof of Lemma 4.3

To prove that:

$$\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq 2m \sqrt{\frac{1}{2^{2n}} \sum_b P\left[\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b\right]} \quad (37)$$

we start with:

$$\sum_{i_T, c_T, b} P(\mathcal{T} = \text{pass}, i_T, c_T, b | s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq m \left(\alpha + \frac{1}{\alpha} \frac{1}{2^{2n}} \sum_b P\left[\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b, s\right] \right).$$

Each order string s must have an equal number of zeros and ones. Aside from that, each are equally likely. So Alice chooses them with $P(s) = \frac{1}{\binom{2n}{n}}$. The right hand side of the average over s of the above equation is:

$$m \left(\alpha + \frac{1}{\alpha} \frac{1}{2^{2n}} \sum_b \left[\frac{1}{\binom{2n}{n}} \sum_s P\left[\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b, s\right] \right] \right)$$

We are now, for each fixed bases b , able to bound each term in the $[]$ parenthesis by a law of large numbers. The probability that a test string will be chosen such that it passes the test, but the remaining information string would not pass the test, given basis b , is written as:

$$P\left(\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b\right) \equiv \frac{1}{\binom{2n}{n}} \sum_s P\left(\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b, s\right)$$

Making use of the above and choosing $\alpha = \frac{1}{2^{2n}} \sum_b P\left[\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b\right]$ to minimize the bound we have the result. Hence,

$$\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq 2m \sqrt{\frac{1}{2^{2n}} \sum_b P\left[\left(\frac{|C_I|}{n} > p_a + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_a\right) | b\right]} \quad (38)$$

QED

L A Proof of Lemma 4.4

In this Appendix let c denote the combination of c_T and c_I , instead of the combination of c_T , c_U and c_I , and let C be the random variable corresponding to c . Let

$$h_b \equiv P\left[\left(\frac{|C_I|}{n} > p_{\text{allowed}} + \epsilon\right) \cap \left(\frac{|C_T|}{n} < p_{\text{allowed}}\right) | b\right]$$

This h_b is the probability that the information has ϵ more than the allowed error rate, when the test has less than the allowed error rate, averaged over all choices of test and information, for a particular basis b .

$$\begin{aligned} h_b &= \sum_{|c|} P\left[\left(\frac{|C_I|}{n} > p_{\text{allowed}} + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_{\text{allowed}}\right) \cap (|C| = |c|) | \text{Basis} = b\right] \\ &= \sum_{|c|} P\left[\left\{\left(\frac{|C_I|}{n} > p_{\text{allowed}} + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p_{\text{allowed}}\right)\right\} \text{ given } |c|, b\right] P(|c| \text{ given } b) \end{aligned}$$

Note that in principle, $P(c|b)$, and hence also $P(|c| \text{ given } b) = P(|C| = |c| \text{ given } b)$ can be calculated, but we shall soon see that there is no need to calculate $P(|c| \text{ given } b)$.

Now we must note that $P\left[\left\{\left(\frac{|C_I|}{n} > p + \epsilon\right) \cap \left(\frac{|C_T|}{n} \leq p\right)\right\} \text{ given } |c|, b\right]$, does not depend on the attack. And in fact, in the aforementioned equation, the basis b is superfluous. Once a basis is fixed, and the numbers of errors given ($|c|$ and b), then we are safely in the hands of random samplings. Any sample choice, of bits for use as information bits will not change $|c|$ or b . Of course c_I , c_T and c are not independent. By definition, $|c| = |c_I| + |c_T|$. If $|c_I| > n(p_{\text{allowed}} + \epsilon)$ and $|c_T| \leq np_{\text{allowed}}$, then $|c_I| - |c_T| > n\epsilon$. So:

$$P\left[\left\{(|c_I| > n(p_{\text{allowed}} + \epsilon)) \cap (|c_T| < np_{\text{allowed}})\right\} \text{ given } |c|, b\right] \leq P\left[\left(|c_I| > \frac{|c|}{2} + \frac{n\epsilon}{2}\right) \text{ given } |c|, b\right]$$

It is the probability that a sampled subset has a weight which is $n\epsilon/2$ more than the average. Intuitively, it may be obvious that the weight of the test string should be equal to half the weight of the full string. By Hoeffding's bound² we make this rigorous (see Appendix M)

$$P(|c_I| > \frac{|c|}{2} + \frac{n\epsilon}{2}) \text{ given } |c|, b \leq 2e^{-\frac{1}{2}n\epsilon^2} . \quad (39)$$

Hence

$$\begin{aligned} h_b &= P\left(\frac{|C_I|}{n} > p_{\text{allowed}} + \epsilon, \frac{|C_T|}{n} < p_{\text{allowed}} \mid \text{Basis} = b\right) \\ &= \sum_{|c|} P\left(\frac{|C_I|}{n} > p_{\text{allowed}} + \epsilon, \frac{|C_T|}{n} \leq p_{\text{allowed}}, \text{ given } |c|, b\right) P(|c| \text{ given } b) \\ &\leq 2e^{-\frac{1}{2}n\epsilon^2} \sum_{|c|} P(|c| \text{ given } b) \\ &= 2e^{-\frac{1}{2}n\epsilon^2} \end{aligned}$$

So finally we summarize the result to be

$$h_b = P\left(\frac{|C_I|}{n} > p_{\text{allowed}} + \epsilon, \frac{|C_T|}{n} < p_{\text{allowed}} \mid \text{Basis} = b\right) \leq 2e^{-\frac{1}{2}n\epsilon^2} . \quad (40)$$

This result for h is useful both for the reliability proof and the security proof.

QED

M Hoeffding

We need to bound the probability $P(|c_I| > \frac{|c|}{2} + \frac{n\epsilon}{2}, \text{ given } |c|)$. Recall that half of the bits are randomly selected to be test bits. This is random sampling without replacement. For the above probability we are given an error string c . Each bit in the error string is either zero or one depending on whether there is or is not an error respectively.

Therefore, $P(|c_I| > \frac{|c|}{2} + \frac{n\epsilon}{2}, \text{ given } |c|)$ is the probability that a sampled average is greater than the entire sample average by more than $\epsilon/2$. This case was studied by Hoeffding [10]. The following bound is given in [11]

$$P\left(\left|\frac{|c_I|}{n} - \frac{|c|}{2n}\right| \geq \epsilon/2\right) \leq 2e^{-\frac{n\epsilon^2}{2}} \quad (41)$$

Note that A in [11] represents c in our notations, m is the sample average $|c|/2n$, and the sum of Z_i is $|c_I|$.

Of course this bound is more restrictive than we need (due to the use of the absolute value). We only need $P(\frac{|c_I|}{n} - \frac{|c|}{2n} \geq \epsilon/2)$, which is smaller than the above bound and therefore the above bound suffices. In fact, from Hoeffding's original paper [10] we can get the bound:

$$P\left(\frac{|c_I|}{n} \geq \frac{|c|}{2n} + \epsilon/2\right) \leq e^{-\frac{n\epsilon^2}{2}} \quad (42)$$

N Satisfying the Security Criterion

So far we have not shown that the security criterion is satisfied by bounding the following:

$$\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} \mid i_T, c_T, b, s) \leq e^{2(\alpha - \beta n)} \quad (43)$$

²BTW - A factor of 2 can be improved.

We now show that when the above bound is satisfied, as shown in the paper, then the security criterion is satisfied:

$$Prob(\text{Test Passes and } I_{Eve} \geq e^{\alpha-\beta n}) \leq e^{\alpha-\beta n} \quad (44)$$

Where $I_{Eve} \equiv I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s)$.

To show the above break the sum into the parts where Eve has large information and the part where she has small. Then standard bounding techniques are used:

$$\begin{aligned} \sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) &= \sum_{\substack{i_T, c_T, b, s \\ s.t. I_{Eve} < I'}} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \\ &+ \sum_{\substack{i_T, c_T, b, s \\ s.t. I_{Eve} \geq I'}} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \\ &\geq \sum_{\substack{i_T, c_T, b, s \\ s.t. I_{Eve} \geq I'}} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \\ &\geq \left(\sum_{\substack{i_T, c_T, b, s \\ s.t. I_{Eve} \geq I'}} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) \right) I' \end{aligned}$$

The above steps follow from non-negativity of probability and mutual information. We are really already done:

$$\left(\sum_{\substack{i_T, c_T, b, s \\ s.t. I_{Eve} \geq I'}} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) \right) I' \leq \sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \quad (45)$$

So far I' is a free parameter. We can set it to any value we like, namely

$$I' = \sqrt{\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s)}:$$

$$\begin{aligned} Prob(\text{Test Passes and } I_{Eve} \geq I') &= \sum_{\substack{i_T, c_T, b, s \\ s.t. I_{Eve} \geq I'}} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) \\ &\leq \sqrt{\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s)} \end{aligned}$$

If we assume that $\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq e^{2(\alpha-\beta n)}$ then we have:

$$Prob(\text{Test Passes and } I_{Eve} \geq e^{\alpha-\beta n}) \leq e^{\alpha-\beta n} \quad (46)$$

Thus, the bounds that we have shown satisfy the security criterion.

O Existence of Codes for Both Reliability and Security

Choosing a code which is good when n is large (for constant error rate) is not a trivial problem in ECC. A Random Linear Code (RLC) is one such code, however, it does not promise us that the distances are as required, but only gives the desired distances with probability as close to one as we want. With RLC, we find that the threshold below which a secure key can be obtained is $p_{allowed} \leq 7.56\%$.

In order to correct t errors with certainty, a code must have a minimal Hamming distance between the code words $d \geq 2t + 1$ so that all original code words, even when distorted by t errors, can still be

identified correctly. For any c_T which passes the test, we are promised (due to Lemma 4.4) that the probability of having $t = |c_I| > n(p_{\text{allowed}} + \epsilon_{\text{rel}})$ errors is smaller than $h = 2e^{-(1/2)n\epsilon_{\text{rel}}^2}$.

Thus, we need to choose a RLC that promises a Hamming distance at least d such that $p_{\text{allowed}} + \epsilon_{\text{rel}} < t/n = \frac{d-1}{2n}$, and then the t errors are corrected except for a probability smaller than $h_1 = 2e^{-(1/2)n\epsilon_{\text{rel}}^2}$.

For any $n, r = n - k$, and for δ such that $H_2(\delta) < r/n$, an arbitrary *random linear code* (n, k, d) satisfies $d/n \geq \delta$, except for a probability (see [9], Theorem 2.2)

$$\text{Prob}(d/n < \delta) \leq \frac{c(\delta)}{\sqrt{n}} 2^{n(H_2(\delta) - r/n)} = g_1 \quad (47)$$

where $c(\delta) = \frac{1}{1-2\delta} \sqrt{\frac{1-\delta}{2\pi\delta}}$.

If we choose $\delta = 2(p_{\text{allowed}} + \epsilon_{\text{rel}}) + 1/n$ then we are promised that the errors are corrected, except for probability that the error rate is larger than expected or a bad code was chosen.

Using such a code, ϵ_{rel} is now a function of δ so that $\epsilon_{\text{rel}} = \delta/2 - 1/(2n) - p_{\text{allowed}}$ and therefore,

$$h_1 = 2e^{-(n/4)(\delta - \frac{1}{n} - 2p_{\text{allowed}})^2} \quad (48)$$

and almost all such codes correct all the errors.

Therefore, the code is reliable except for a probability $g_1 + h_1$.

The above result can be improved [8] by taking RLC with distance $d - 1 \geq n(p_{\text{allowed}} + \epsilon_{\text{rel}})$ (without the factor of 2), since such a code can also correct $t = n(p_{\text{allowed}} + \epsilon_{\text{rel}})$ errors except for an exponentially small fraction f_1 of the possible errors. We get

$$f_1 = 2e^{-(n/4)(\delta - \frac{1}{n} - p_{\text{allowed}})^2} \quad (49)$$

and it is exponentially small (in the limit of large n) for any $\delta > p_{\text{allowed}}$.

Recall that we choose ϵ_{sec} such that $|v| \geq 2n(p_{\text{allowed}} + \epsilon_{\text{sec}})$. Let $|v|$ be the minimal distance between one PA string and any other parity check string (or linear combination) taken from ECC and PA. Clearly, the Hamming weight of the dual code of the ECC, once the PA is also added, provides a lower bound on $|v|$. Thus, it is sufficient to demand $d^\perp \geq 2n(p_{\text{allowed}} + \epsilon_{\text{sec}})$ in order to prove security. Choosing a RLC for the ECC and PA, one cannot be completely sure that the distance indeed satisfies the constraint, but this shall be true with probability exponentially close to one. We use the dual code $(n, r^\perp, d^\perp)$, where $r^\perp = n - r - m$. Such codes satisfy $d^\perp/n \geq \delta^\perp$, except for a fraction of

$$\text{Prob}(d^\perp/n < \delta^\perp) \leq \frac{c(\delta^\perp)}{\sqrt{n}} 2^{n(H_2(\delta^\perp) - (n-r-m)/n)} = g_2 \quad (50)$$

With $\delta^\perp = 2(p_{\text{allowed}} + \epsilon_{\text{sec}})$.

Assuming that Eve gets full information when the code fails we get:

$$\sum_{i_T, c_T, b, s} P(\mathcal{T} = \text{pass}, i_T, c_T, b, s) I(\mathcal{A}; \mathcal{E} | i_T, c_T, b, s) \leq m \left(2\sqrt{2e^{-\frac{1}{2}n\epsilon_{\text{sec}}^2}} + g_2 \right) \quad (51)$$

Since the first term is exponentially small we only need look at g_2 . We also need to worry about the reliability so we need g_1 and f_1 to be exponentially small as well. All of them are exponentially small if the following conditions are met:

$$\begin{aligned} H_2(\delta) - r/n &< 0 \\ H_2(\delta^\perp) + r/n + m/n - 1 &< 0 \end{aligned}$$

Or written another way:

$$\begin{aligned} H_2(p_{\text{allowed}} + \epsilon_{\text{rel}} + 1/n) &< r/n \\ H_2(2p_{\text{allowed}} + 2\epsilon_{\text{sec}}) + H_2(p_{\text{allowed}} + \epsilon_{\text{rel}} + 1/n) &< 1 - R_{\text{secret}} \end{aligned}$$

Where $R_{\text{secret}} \equiv m/n$. In the limit of large n and ϵ 's close to zero, $p_{\text{allowed}} < 7.56\%$ satisfies the bound and hence this is our threshold.

Asymptotically, any $R_{\text{secret}} < 1 - H_2(2p_a) - H_2(p_a)$ is secure and reliable for the given ECC+PA. Note, as p_a goes to zero, R_{secret} goes to 1, which means all the information bits are secret.

This threshold is based on the property of the code, and other codes might give worse thresholds. It is possible to replace the RLC by a code that can be decoded and encoded efficiently (e.g., Reed-Solomon concatenated code), and add random PA strings. The Hamming distance between the PA check-strings and the ECC check-strings is still bounded below in the same way as for the RLC (see [8]).

A better threshold can be obtained by using privacy-distillation instead of the standard ECC+PA approach.

Note that any probability of failure in the classical transmission can be added in the same way that g_2 is added. This is important to prove security in the case where a fault-tolerant classical transmission is not 100% reliable. It shows an important advantage over the proof of [14] which is based on fault tolerant quantum ECC.